

MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918
Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com

www.mikroe.com

## **SHT AN Click**





PID: MIKROE-3984

**SHT AN Click** is a sensorics based add on board which can be used for measuring humidity and temperature. It features fully calibrated, linearized and temperature compensated <a href="SHT31-ARP-B">SHT31-ARP-B</a> sensor with analog output. This sensor is built on a new technology CMOSens® sensor chip from <a href="Sensirion">Sensirion</a>. What differentiate this Click board comparing to other is dual sensor analog output which can be used for measuring and calculation of the data over one analog output. This board is best suitable for the smart and low power applications which require temperature range of -40 to up to 90 °C. We have also in our offer SHT Click, which is a digital interface version of the same sensor.

SHT AN Click is supported by a mikroSDK compliant library, which includes functions that simplify software development. This Click board $^{\text{\tiny M}}$  comes as a fully tested product, ready to be used on a system equipped with the mikroBUS $^{\text{\tiny M}}$  socket.

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.





health and safety management system.



MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918 Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com www.mikroe.com

## **Specifications**

Туре	Temperature & humidity
Applications	Industrial RH and temperature measuring applications, smart home, air conditioner, home and environmental monitoring, etc
On-board modules	SHT AN Click uses the SHT31-ARP, a high accuracy temperature and humidity sensor from Sensirion.
Key Features	Key Features Low energy consumption, wide temperature and humidity operating range with low RH response time, small package
Interface	Analog,GPIO
ClickID	No
Compatibility	mikroBUS
Click board size	S (28.6 x 25.4 mm)
Input Voltage	3.3V or 5V

## Resources

<u>mikroBUS™</u>

**mikroSDK** 

Click board™ Catalog

Click Boards™

## **Downloads**

SHT AN click example on Libstock

SHT AN click 2D and 3D files

SHT31-ARP datasheet

**SHT AN click schematic** 

Mikroe produces entire development toolchains for all major microcontroller architectures. Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.





health and safety management system.