



Metric table

Dimensions in: millimeters - inches

| ¹ d ₁ | ² d ₂ Thread | | d ₃ | h ₁ | h ₂ | h ₃ | s | t |
|-----------------------------|---------------------------------------|------|----------------|----------------|----------------|----------------|------------|-----------|
| 34 1.34 | M 6 | - | 17 .67 | 22 .87 | 20 .79 | 12 .47 | 7 .28 | 9 .35 |
| 45 1.77 | M 8 | - | 25 .98 | 30 1.18 | 27 1.06 | 18 .71 | 8.5 .33 | 14 .55 |
| 65 2.56 | M 8 | - | 30 1.18 | 39 1.54 | 36 1.42 | 25 .98 | 10 .39 | 14 .55 |
| 65 2.56 | M 10 | - | 30 1.18 | 39 1.54 | 36 1.42 | 25 .98 | 10 .39 | 15 .59 |
| 85 3.35 | M 8 | M 10 | 35 1.38 | 48 1.89 | 43 1.69 | 30 1.18 | 12 .47 | 17 .67 |

Specification

- Three-lobed knob
Phenolic plastic
 - Temperature resistant up to 300 °F (150 °C)
 - Black, shiny finish
- Tapped insert
Brass, molded-in
- RoHS compliant

Information

3P-B three-lobed knobs have an aesthetically pleasing shape and provide a comfortable grip. Resistant to solvents, oils, grease and other chemical agents.

see also...

- Three Lobed Knobs 3P-P (with Steel Threaded Stud)

| | | |
|-------------------------------------------------------------------------------|---|--------------------------------|
| <p>How to order</p> <p>¹ ²</p> <p>3P-B-85-M8</p> | 1 | Handle diameter d ₁ |
| | 2 | Thread d ₂ |