

## Specification Sheet

Part Number: 151-01126

Clip can be installed by hand – no need for hardware or tools.  
Design provides low insertion and high extraction force, for simple, secure performance.

Product Image

Clip keeps bundle away from areas that could cause damage due to rubbing.

Standoff Bundling Clip, 1.7" Long, Panel Thickness .02 - 0.23", PA66HIRHSUV, Black, 5000/box

Article Number 151-01126

Type SOC13FT6LGR

Color Black (BK)

Quantity Per carton

Product Description Standoff bundling clips provide a straightforward way to secure cable bundles, hoses or pipes. The bundle fastens to the tape bar using tape or cable ties. Multiple orientations allow tape clips to be used with a wide range of panel thicknesses and hole diameters. Standoff keeps bundles away from mounting area to prevent them from damage due to rubbing.

Short Description Standoff Bundling Clip, 1.7" Long, Panel Thickness .02 - 0.23", PA66HIRHSUV, Black, 5000/box

Global Part Name SOC13FT6LGR-PA66HIRHSUV-BK

Length L (Imperial)	1.7
Length L (Metric)	43.2
Offset Length (Imperial)	0.8
Offset Length (Metric)	20.3
Fixation Method	Fir Tree
Width W (Imperial)	0.87
Width W (Metric)	22.0
Height H (Imperial)	1.33
Height H (Metric)	33.7
Panel Thickness Min (Imperial)	0.02
Panel Thickness Max (Imperial)	0.23
Panel Thickness Min (Metric)	0.51
Panel Thickness Max (Metric)	5.8
Mounting Hole Diameter D (Imperial)	0.24 - 0.27
Mounting Hole Diameter D (Metric)	6.1 - 6.9 mm
Mounting Hole Diameter D Min (Imperial)	0.24
Mounting Hole Diameter D Max (Imperial)	0.27

Mounting Hole Diameter D Max (Metric)	6.9
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
UV Resistant (Yes/No)	Yes
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	No
Package Quantity (Imperial)	5003
Package Quantity (Metric)	5000
Customs Number	3926909988

## About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. ([www.hellermann.tyton.com](http://www.hellermann.tyton.com)).