

External insulated cross-connector, No. of poles: 3, Mounting type: Plug in, Width: 14.36 mm, Rated current: 27 A; Colour: Yellow

RAL: 1026

Business data

Article number	2024.0
Article name	AQI 3/5/15 YE
GTIN (EAN)	4044211048273
Packaging unit	50
Quantity unit	PC
Weight per piece (not including packaging)	1.22 g
Weight per piece (including packaging)	1.23 g
Unit of weight	G
Customs number	85389099
Country of origin	DE
Prio-Article	2024.0
Product description	External insulated cross-connector

Technical data

Dimensions

Width	14.36 mm
-------	----------

Pitch size	5 mm
------------	------

Ratings

Rated current	27 A
---------------	------

Contamination degree	3
----------------------	---

Connection data

No. of poles	3
--------------	---

Materials

Material	Copper
----------	--------

Surface	Tin-plated
---------	------------

Insulation housing	Polyamide 6.6
--------------------	---------------

Flammability class UL 94	V-2
--------------------------	-----

Working temperature, min.	-40 °C
---------------------------	--------

Working temperature, max.	105 °C
---------------------------	--------

Further technical data

Mounting type	Plug in
---------------	---------

Insulation available	✓
----------------------	---

Touch protection is available	✓
-------------------------------	---

Number of bridged terminals	3
-----------------------------	---

Environmental Product Compliance

REACH Conform	Yes
---------------	-----

REACH Candidate Substance Note	No
--------------------------------	----

RoHS Conform	Yes
--------------	-----

Media

Accessories

##INVERSE##CONTA-CONNECT



Motor-connection terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>3582.2</u>	ZVMAK 2,5 BG	4044211059309	50



Motor-connection terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>3646.2</u>	ZVMAK 2,5 N/L/L/PE BG	4044211171322	50 ST



Double-level terminal/block variant, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>1208.2</u>	KBLD 2,5 m.B. BG	4044211028374	10 ST




Feed-through terminal/block variant, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>1298.2</u>	KBL 2,5 m.B. BG	4044211040499	10 ST



Feed-through terminal for direct mount/block variant, Screw connection, Mounting type: Mounting surface, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>1387.2</u>	KBL 2,5-D BG	4044211044282	100



Double-level terminal/block variant, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>1207.2</u>	KBLD 2,5 BG	4044211028282	10 ST

##INVERSE##CONTA-CONNECT



Feed-through terminal/block variant, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>1297.2</u>	KBL 2,5 BG	4044211040383	10 ST



Feed-through terminal for direct mount/block variant, Screw connection, Mounting type: Mounting surface, Rated cross-section: 2.5 mm², Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>1384.2</u>	KBL 2,5/10-D BG	4044211044251	10