#### - Cinch Connectors - http://www.cinch.com -

### Accessories - Screwlocks

# Features [1] | Part Numbers [2]

#### **Features**

#### Screwlocks

- Screwlocks are designed to retain the same size mated connectors together or to secure the connector to a rack/panel. Screwlocks may be used on plugs or sockets.
- Female screwlocks consists of one #4-40 hole in the top, two flat washers to accommodate different panel thicknesses, one lockwasher, and one #4-40 nut. Military female screwlocks include three flat washers.
- Male screwlocks consit of one #4-40 slotted screw and a spring tension clip. Different sizes
  accommodate the various connector flange sizes and types of backshells or hoods (if
  applicable).
- Two screwlocks are required per connector.
- Military screwlocks meet all rquirements of MIL-C-24308.

#### **Materials**

### **Commercial Screwlock Assemblies**

- Male Screwlock Assembly: Clip and screw are steel with zinc plating and yellow chromate finish
   RoHS parts have clear chromate in place of yellow chromate.
- Female Screwlock Assembly: Washers (2), lockwashers, hex nuts, and nuts are steel with zinc plating and yellow chromate finish. RoHS parts have clear chromate finish.

### **M24308 Military Screwlock Assemblies**

- Male Screwlock Assembly: Clip and screw are steel with cadmium plating and yellow chromate finish
- Female Screwlock Assembly: Washers (3), lockwashers, hex nuts, and nuts are steel with cadmium plating and yellow chromate finish.

back to top [3]

## **Part Numbers**

# Male Screwlocks - Ordering Information

| Shell Size |              | l l   | A    | В     | 3    | Е   | Α   | В    | С    | D    |
|------------|--------------|-------|------|-------|------|-----|-----|------|------|------|
| Positions  |              | in    | mm   | in    | mm   | 9   | 15  | 25   | 37   | 50   |
| COMMERCIAL | RoHS Version |       |      |       |      |     |     |      |      |      |
| D20419-0   | D20419-40    | 0.250 | 6.35 | 0.033 | 0.84 | P/S | P/S | S    | S    |      |
| D20419-16  | D20419-46    | 0.250 | 6.35 | 0.048 | 1.22 | S*  | S*  | P/S* | P/S* |      |
| D20419-21  | N/A          | 0.281 | 7.13 | 0.059 | 1.50 |     | P*  | P*   |      |      |
| D20420-0   | N/A          | 0.250 | 6.35 | 0.033 | 0.84 |     |     |      |      | S    |
| D20420-12  | D20420-42    | 0.281 | 7.13 | 0.048 | 1.22 |     |     |      |      | P/S* |
| D20420-15  | N/A          | 0.281 | 7.13 | 0.059 |      |     |     |      |      | P*   |
|            |              |       |      |       |      |     |     |      |      |      |

| MILITARY MIL-C-24308 |              |  |     |     |     |     |     |
|----------------------|--------------|--|-----|-----|-----|-----|-----|
| M24308/25-9F         | Per MIL Spec |  | P/S | P/S | P/S | P/S |     |
| M24308/25-10F        | Per MIL Spec |  |     |     |     |     | P/S |

Note: P=Plug, S=Socket \*Indicates used with Junction shell

# **Female Screwlocks - Ordering Information**

| Shell Size           |              | А     |       | Е   | A   | В   | С   | D   |
|----------------------|--------------|-------|-------|-----|-----|-----|-----|-----|
| Positions            |              | in    | mm    | 9   | 15  | 25  | 37  | 50  |
| COMMERCIAL           | RoHS Version |       |       |     |     |     |     |     |
| D20418-2             | D20418-42    | 0.312 | 7.92  | P/S | P/S | P/S | P/S | P/S |
| D20418-39            | N/A          | 0.628 | 15.95 | P/S | P/S | P/S | P/S | P/S |
| MILITARY MIL-C-24308 |              |       |       |     |     |     |     |     |
| M24308/26-1F         | Per MIL Spec |       |       | P/S | P/S | P/S | P/S | P/S |
| M24308/26-2F         | Per MIL Spec |       |       | P/S | P/S | P/S | P/S | P/S |

Note: P=Plug, S=Socket

Article printed from Cinch Connectors: http://www.cinch.com

URL to article: http://www.cinch.com/products/d-subminiature/under-accessories-screwlocks-slide-locks

URLs in this post:

[1] Features: #features[2] Part Numbers: #parts[3] back to top: #top

Copyright © 2010 Cinch Connectors. All rights reserved.