

Series **D XX S 24B 6 XX 12 LF**

Number of contacts
09 , 15 , 25

Contacts
S : Socket

Plating
6 = 500 Mating / Unmating Mini

Packaging specification
Tape & Reel

See Note RoHS

Termination

Code	Type	Foot Print/Pitch	Length of termination	PCB thickness
24B	Straight version	6 / 2.84mm	2.90	2.4

Mounting Options

RL	Insert M3
RV	Female Screw UNC 4-40
RX	Insert UNC 4-40

NOTE RoHS INFORMATION

- The "LF" product meet european union Directives and other country regulations asdescribed in GS-22-008.
- The housing will whistand exposure to 260^o peak temperature for 30 seconds in a convection , infra-red or vapor reflow oven. See application notes/procedures if are available.
- Termination plating spec:1.27 μ Nickel mini,2.5 to 7.5 μ Sn(pure mate)
- Shell plating : Nickel bright
- Accessories : Sn pure bright
- Packaging spec ; See GS-14-920



Product Specification

see : GS-12-372

Packaging Specification

See GS-14-1054

ltr	ecn no	dr	date
I	CREATED	HLE	06/08/24
A	LS06-0223	PCR	2006/12/21
B	110-0120	NG	2010-05-27
C	110-0197	NG	2010-10-14
-	-	-	-
-	-	-	-
-	-	-	-

www.fciconnect.com		surface <input checked="" type="checkbox"/> ISO 1302	tolerance std <input checked="" type="checkbox"/> ISO 406 <input type="checkbox"/> ISO 1101	projection 	mm 
TOLERANCES UNLESS OTHERWISE SPECIFIED					
Dr	P. CRON	02/02/06	ANGULAR	LINEAR	size A3
Eng	H. LEGALLIC	02/02/06	0°	±2°	Scale 3:1
Chr	NIRMAL G	2010-10-14	0.X	±0.3	ECN 110-0197
Appr	SUDHIR V	2010-10-14	0.XX	±0.1	Spec ref -
			0.XXX	±0.05	
FCi		SUB DELTA D PIP FEMALE H=2		customer C01-8646-0886	Rev. C
		straight for tape and reel packaging		customer	sheet 1 of 2
		catalog no SEE TABLE			

