


EVF551



Ethernet connection cable

VSTGN040VAS0002P04STGP040--S



Application

| | |
|--------------------|--|
| Special feature | Free from silicone; Halogen-free; Gold-plated contacts; Screened cable; Drag chain suitability |
| Design | Ethernet cable, D-coded |
| Application | Industrial Ethernet; CAT5/CAT5e; 100 Mbit/s; hygienic and wet areas in the food industry |
| Free from silicone | yes |

Electrical data

| | | |
|-------------------------|-----|---------------|
| Operating voltage | [V] | 30 AC / 60 DC |
| Protection class | | III |
| Max. current load total | [A] | 1.5 |

Operating conditions

| | | |
|------------------------------|------|--|
| Ambient temperature | [°C] | -25...100 |
| Ambient temperature (moving) | [°C] | 0...80 |
| Protection | | IP 65; IP 67; IP 68; IP 69K; (M12 plug / RJ45 plug: IP 20) |

Mechanical data

| | | |
|------------------------|-----|---|
| Weight | [g] | 152.8 |
| Materials | | brass nickel-plated; housing: PP Halogen-free |
| Moulded-body material | | PP / PC |
| Material nut | | stainless steel (1.4404 / 316L) |
| Drag chain suitability | | yes |

EVF551



Ethernet connection cable

VSTGN040VAS0002P04STGP040--S

| | | |
|------------------------|---------------------------------|--|
| Drag chain suitability | bending radius for flexible use | min. 15 x cable diameter |
| | travel speed | max. 3.3 m/s for a horizontal travel length of 5 m and max. acceleration of 5 m/s ² |
| | bending cycles | > 1 Mio. |
| | torsional strain | ± 180 °/m |

Remarks

Pack quantity 1 pcs.

Electrical connection - plug M12


Connector: 1 x M12, straight; coding: D; Moulded body: PP; Locking: stainless steel (1.4404 / 316L); Contacts: gold-plated; Tightening torque: 0.6...1.2 Nm



Electrical connection

Cable: 2 m, MPPE, Halogen-free, grey, Ø 6.5 mm, shielded; PROFINET Type C; 4 x 0.34 mm² (7 x Ø 0.25 mm)

Connection



Electrical connection - plug RJ45

Connector: 1 x RJ45, straight; Moulded body: PC; Contacts: gold-plated

