## **HellermannTyton**

## **Specification Sheet**

Part Number: TSRP3W-14

Tamper resistant covers with hidden latch provide security while allowing quick entry for cable maintenance.

PVC construction is lightweight, durable and more affordable than metallic raceway systems.

Flexible hinge designed to reduce stress cracking and discoloration from repeated opening and closing.

Systems and fittings are available in white, office white and ivory to coordinate with a variety of décor.

Fittings incorporate a minimum 1" bend radius to meet TIA/EIA 568-B and 569-A standards.



TSRP power rated surface raceway systems have an enhanced "channel and lug" mating design that provides a tighter, more secure fit between raceway lengths and fittings, enabling the system to be UL Listed for power up to 600 volts and meet UL5A and CSA 22.2.

Splice Cover, 1-3/4", PVC, 3-Piece, White, 10 Individual/bg

Article Number250-63142TypeTSRP3-14ColorWhite (WH)Quantity PerEA

| Product Description          | HellermannTyton surface raceway systems are the ideal solution for<br>routing communication and power cables. No need to break into<br>existing walls - raceway systems are designed to route cable along wall<br>surfaces. Made of a PVC material, components are durable and<br>affordable; and the one piece construction and adhesive tape backing<br>make positioning and mounting easy. HellermannTyton offers a low<br>voltage TSR system and a power rated TSRP system that are available<br>in three different diameters to accommodate different cable and wire<br>bundle and conduit sizes. Both systems include a complete line of<br>fittings and junction boxes that allow for clean and professional<br>installations. TSRP surface raceway systems are designed to<br>aesthetically organize and route either power or communications<br>cables. |
|------------------------------|--|
| Short Description            | Splice Cover, 1-3/4", PVC, 3-Piece, White, 10 Individual/bg  |
| Global Part Name             | TSRP3-14-PVC-WH  |
|                              |  |
| Material                     | Polyvinylchloride (PVC)  |
| Material Shortcut            | PVC  |
| Flammability                 | UL 94 V-0  |
| Halogen Free                 | No   |
| UV Resistant (Yes/No)        | No   |
| Operating Temperature        | +122°F (+50°C)   |
| Reach Compliant (Article 33) | No   |
| ROHS Compliant               | Yes  |
| UL Listed (US and Canada)    | Yes  |

| UL Listed (US)              | Yes        |
|-----------------------------|------------|
|                             |            |
| Package Quantity (Imperial) | 10         |
| Package Quantity (Metric)   | 10         |
| Customs Number              | 3925900000 |

## About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved. Contact Us **RoHS/WEEE** Compliance Disclaimer Terms and Conditions