

# Han F+B housing bulkhead mount-angled



Part number	09 15 503 0901
Specification	Han F+B housing bulkhead mount- angled
HARTING eCatalogue	https://b2b.harting.com/09155030901

Image is for illustration purposes only. Please refer to product description.

### Identification

Category	Hoods/Housings
Series	Han <sup>®</sup> F+B
Type of hood/housing	Bulkhead mounted housing
Description of hood/housing	Angled With three through holes for fixing screws

#### Version

Locking type	Screw locking
Field of application	Connector for food+beverage industry
Details	Cleaning: For cleaning with high pressure lances, a cleaning distance > 30 cm is recommended in order to avoid mechanical damage to the connector's exterior parts.
	Strain relief:A suitable strain relief is required to enable the F+B connectorto resist the stress caused e.g. by the daily cleaning of the machinery. DIN VDE 0100-520: 2013-06 defines the stress relief for a connector depending on the outer diameter of the cable.

#### Technical characteristics

Limiting temperature	-40 +125 °C
Note on the limiting temperature	For use as a connector according to IEC 61984.
Mating cycles	≥500
Degree of protection acc. to IEC 60529	IP67 locked condition IP6K9K acc. to ISO 20653

# Material properties

|--|



# Material properties

Roughness of the surface	≤1.12 µm
Colour (hood/housing)	Black
Material (seal)	EPDM Silicone
Colour (seal)	Blue
Material flammability class acc. to UL 94	НВ
RoHS	compliant
ELV status	compliant
China RoHS	е
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
EG1935/2004	compliant
California Proposition 65 substances	Yes
California Proposition 65 substances	Naphthalene

# Specifications and approvals

CE	Yes
Approvals	Ecolab Topactive 200 Ecolab Topactive 500
	Ecolab Topax 66
	Ecolab Topactive OKTO
	Ecolab Topax 990
	FDA 21 CFR 177.1520
	FDA 21 CFR 177.2600

### Commercial data

1
29.72 g
Germany
85389099
5713140023611
27440202 Shell for industrial connectors