## SIEMENS

## Data sheet

## US2:52BP2JT



30mm BlackMax, Epoxy Coated Corrosion Resistant Complete Metal Unit Illuminated Push-Pull Operator Transformer type, 480V AC Incandescent Lamp Mushroom Head Cap Small 1 3/4" (44.5 mm) Plastic, Amber 2 Position Maintained, Pull-to-Release UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards

design of the product	Actuator round
Enclosure	
number of command points	1
delivery state as a kit	No
Actuator	
product extension optional light source	Yes
color of the actuating element	amber
material of the actuating element	plastic
type of unlocking device	pull-to-unlatch mechanism
number of switching positions	2
Front ring	
product component front ring	Yes
design of the front ring	standard
material of the front ring	metal
color of the front ring	black
Holder	
material of the holder	Metal
Contact block/ lampholder	
socket design	BA 9s with lamp
number of lampholders	1
Display	
number of LED modules	0
General technical data	
product component	
lamp transformer	Yes
light source	Yes
degree of pollution	1
type of voltage	
<ul> <li>of the operating voltage</li> </ul>	AC
<ul> <li>of the input voltage</li> </ul>	AC
surge voltage resistance rated value	4 kV
protection class IP	IP66
of the terminal	IP20
Supply voltage	
type of voltage of the supply voltage of the light source	AC
supply voltage of the light source at AC at 60 Hz	
rated value	6 V
Inputs/ Outputs	
output voltage 1 of the lamp transformer rated value	6 V
Connections/ Terminals	

type of electrical connection       screw-type terminals         • of modules and accessories       Screw-type terminal         tightening torque of the screws in the bracket       20 N·m         tightening torque [lbf:in] with screw-type terminals       8 8 lbf-in         Lamp       filament lamp         color of the light source       clear         Safety related data       clear         touch protection against electrical shock       finger-safe         Ambient conditions       -35 +70 °C         auting operation       -35 +70 °C         burg storage       -40 +85 °C         Installation/ mounting/ dimensions       shape of the installation opening         round       Certificates/ approvals		
tightening torque of the screws in the bracket       20 N·m         tightening torque [lbf-in] with screw-type terminals       8 8 lbf-in         Lamp       filament lamp         color of the light source       clear         Safety related data       color protection against electrical shock         touch protection against electrical shock       finger-safe         Ambient conditions       -35 +70 °C         ambient temperature       -40 +85 °C         Installation / mounting/ dimensions       shape of the installation opening         round       Certificates/ approvals         Further information       Siemens has decided to exit the Russian market (see here).		
tightening torque [lbf-in] with screw-type terminals       8 8 lbf-in         Lamp       filament lamp         type of light source       clear         Safety related data       clear         touch protection against electrical shock       finger-safe         Ambient conditions       -35 +70 °C         ambient temperature       -40 +85 °C         Installation/ mounting/ dimensions       round         Shape of the installation opening       round         Certificates/ approvals       Further information         Siemens has decided to exit the Russian market (see here).       Semens has decided to exit the Russian market (see here).		
Lamp       filament lamp         type of light source       filament lamp         color of the light source       clear         Safety related data       clear         touch protection against electrical shock       finger-safe         Ambient conditions       ambient temperature         • during operation       -35 +70 °C         • during storage       -40 +85 °C         Installation/ mounting/ dimensions       shape of the installation opening         round       Certificates/ approvals         Further information       Siemens has decided to exit the Russian market (see here).		
type of light source       filament lamp         color of the light source       clear         Safety related data       clear         touch protection against electrical shock       finger-safe         Ambient conditions       ambient temperature         • during operation       -35 +70 °C         • during storage       -40 +85 °C         Installation/ mounting/ dimensions       round         Shape of the installation opening       round         Certificates/ approvals       Further information         Siemens has decided to exit the Russian market (see here).       Eventer		
color of the light source       clear         Safety related data		
Safety related data         touch protection against electrical shock       finger-safe         Ambient conditions         ambient temperature <ul> <li>during operation</li> <li>-35 +70 °C</li> <li>during storage</li> <li>-40 +85 °C</li> </ul> Installation/ mounting/ dimensions         shape of the installation opening       round         Certificates/ approvals         Further information         Siemens has decided to exit the Russian market (see here).		
touch protection against electrical shock       finger-safe         Ambient conditions       ambient temperature         • during operation       -35 +70 °C         • during storage       -40 +85 °C         Installation/ mounting/ dimensions       shape of the installation opening         round       Certificates/ approvals         Further information       Siemens has decided to exit the Russian market (see here).		
Ambient conditions         ambient temperature         • during operation         • during storage         -40 +70 °C         • during storage         -40 +85 °C         Installation/ mounting/ dimensions         shape of the installation opening         round         Certificates/ approvals         Further information         Siemens has decided to exit the Russian market (see here).		
ambient temperature     -35 +70 °C       • during operation     -35 +70 °C       • during storage     -40 +85 °C       Installation/ mounting/ dimensions     -40 +85 °C       shape of the installation opening     round       Certificates/ approvals     Further information       Further information     Siemens has decided to exit the Russian market (see here).		
Installation/ mounting/ dimensions shape of the installation opening Certificates/ approvals Further information Siemens has decided to exit the Russian market (see here).		
shape of the installation opening     round       Certificates/ approvals       Further information       Siemens has decided to exit the Russian market (see here).		
Certificates/ approvals Further information Siemens has decided to exit the Russian market (see here).		
Further information Siemens has decided to exit the Russian market (see here).		
Siemens has decided to exit the Russian market (see here).		
https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business		
Siemens is working on the renewal of the current EAC certificates. Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to	e products to an	
EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).		
Information on the packaging		
https://support.industry.siemens.com/cs/ww/en/view/109813875		
Information- and Downloadcenter (Catalogs, Brochures,)		
https://www.siemens.com/ic10		
Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52BP2JT		
Cax online generator		
http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52BP2JT		
Service&Support (Manuals, Certificates, Characteristics, FAQs,)		
https://support.industry.siemens.com/cs/ww/en/ps/US2:52BP2JT		
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros,)		
http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52BP2JT⟨=en		

last modified:

5/31/2021 🖸