## ATGBICS FTL4C2QE2C Finisar Compatible Transceiver QSFP+ 40GBase-LM4 (1310nm, MMF, 1km, DOM)

Brand : ATGBICS Product code: FTL4C2QE2C-C

**Product name :** FTL4C2QE2C Finisar Compatible Transceiver QSFP+ 40GBase-LM4 (1310nm, MMF, 1km, DOM)



FTL4C2QE2C Finisar Compatible Transceiver QSFP+ 40GBase-LM4 (1310nm, MMF, 1km, DOM)

ATGBICS FTL4C2QE2C Finisar Compatible Transceiver QSFP+ 40GBase-LM4 (1310nm, MMF, 1km, DOM):

ATGBICS FTL4C2QE2C 40GBase-LM4 supports a distance of up to 1km over multi mode fibre (MMF) using a wavelength of 1310nm via an LC connector. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product meets the specification of Finisar FTL4C2QE2C= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.



Performance		Features	
SFP transceiver type *	Fiber optic	Certification	CE, FCC, RoHS
Maximum data transfer rate * 40000 Mbit/s Interface type * QSFP+ Single-mode fiber (SMF) supported * Multi-mode fiber (MMF) supported Fiber optic connector LC SFP transceiver standard LM4 Maximum transfer distance 1000 m Wavelength 1310 nm Ethernet LAN		Power	
	Input voltage Maximum voltage Power consumption (typical)	3.3 V 3.5 V 3.5 W	
	Operational conditions  Maximum operating temperature Operating temperature (T-T)	70 °C 0 - 70 °C	
	Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	-40 - 85 °C 0 - 95% 0 - 95%	
(DDM) Wavelength-division multiplexing (WDM)	×	Weight & dimensions Width	13.5 mm
Features		Depth	72.4 mm
Product colour Housing material		Height Weight	18.4 mm 42 g
Plug and Play	<b>/</b>	Packaging data	
ot-Plug support  ot-swap	<b>4</b>	Number of products included Package type	1 pc(s) Box
Easy to install	intry of origin China	Technical details	
Country of origin Brand compatibility		Sustainability compliance Sustainability certificates Doesn't contain	<b>√</b> RoHS Lead



5056468762047

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.