

Domestic Applications to BS1361 & BS1312

**Consumer Unit Fuse Link
240V / 5 - 45 A**



Specifications

Description: Cylindrical Fuse Links for domestic application according to BS1361

Ratings:

Volts: - 240V
Amps: - 5 - 45A
IR - 16.5kA

Applications: Protection of domestic distribution systems.


Agency Information: Approved to BS1361

Catalogue Numbers

| Rating (A) | Catalogue Number | Colour Code | Unit Packing |
|------------|------------------|-------------|--------------|
| 5 | C55 | White | 10 |
| 15 | C1515 | Blue | |
| 20 | C1520 | Yellow | |
| 30 | C3030 | Red | |
| 45 | C4545 | Green | |

BK (Part Number), Unit packing = 100

Dimensions



| Catalogue Number | A | B |
|------------------|-------|----|
| C55 | 5.35 | 23 |
| C1515 | 10.2 | 26 |
| C1520 | 10.32 | 26 |
| C3030 | 12.7 | 29 |
| C4545 | 16.67 | 35 |

**Plug Top Fuse Links
240V / 1 - 13A**



Specifications

Description: Cylindrical Fuse links for domestic applications according to BS1362, to be fitted into domestic BS1363 plug top to conform with the requirements of the Plug and Socket Safety Regulations 1995

Ratings:

Volts: - 240V
Amps: - 1 - 13A
IR - 6kA

Applications: protection of the cables connected to domestic equipment against overloads or small overcurrents.

Agency Information: BSI Kite Mark, ASTA accreditation (except 1A Fuse), BS1362


RoHS Compliant

Catalogue Numbers

| Rating (A) | Catalogue Number | Colour Code | Unit Packing |
|------------|------------------|-------------|--------------|
| 1 | C180-1A | Black | 10 |
| 2 | C180-2A | Black | |
| 3 | C180-3A | Red | |
| 5 | C180-5A | Black | |
| 7 | C180-7A | Black | |
| 10 | C180-10A | Black | |
| 13 | C180-13A | Black | |

BK-(Part Number), Unit packing= 100

Dimensions



| Catalogue Number | A | B |
|------------------|------|------|
| C180-RatingA | 6.45 | 25.4 |