72 INCHES LENGTH



Connector A 132114 SMA Plug Straight Brass Gold + Heatshrink 50 Ohm RG-174 Continuity/Hi-Pot Connector B 112234 BNC Jack Straight Bulkhead - Rear Mount Brass Nickel

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

De Tyj Ge Bo Co Po Imj Mo Bo	lescription: S ype: S Sender: P Kody Type: S contact Type: S folarity: S npedance: 5	32114 MA PLUG RG174 MA Plug Itraight isolder Standard 0 Ohm	4 RG316 LMR100 50O	Part #: Description: Dielectric: Shielding: Diameter: Impedance:	RG-174 RG-174 - PE 0.1 PE Braid 0.1 50 Ohm	Part #: Description: Type: Gender: Body Type:	112234 BNC Clamp BHD JK BNC Jack Straight	RG188 500
IP Co Co Ma	Body Material: B Body Finish: G P Rating: N Contact Material: B Bontact Finish: G Iax. Freq.: 1	Cable Grass Gold Jone Grass Gold 2.4 GHz	RG316 LMR100 50O	Description:RCDielectric:PEShielding:BrDiameter:0.1Impedance:50Sheathing:NoTesting:Co	None Continuity Hi-Pot 72 Inches	Contact Type: Polarity: Impedance: Mounting: Body Material: Body Finish: IP Rating: Contact Material: Contact Finish: Max. Freq.: Booting:	Crimp Standard 50 Ohm Bulkhead - Rear Mo Brass Nickel None Beryllium Copper Silver 4 GHz	
Во	Booting: SMA Plug Straigh		I			Booting: Clocking:	•	
Amphenol CUSTOM CABLE			THIS DRAWING MAY CONTAIN PROPRIETARY INFORMATION A FOR ANY PURPOSE DETRIMENT INC. IT MAY NOT BE REPRODUC IN ANY FORM WITHOUT THE W CUSTOM CABLE INC. ACCEPTA	AND MUST NOT BE US FAL TO CUSTOM CAB CED OR TRANSCRIBE /RITTEN CONSENT OF	LE D	Title: SMA-ST-PL/BNC-ST-JK G174 72I		UNLESS SPECIFIED TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: CENTER LABEL IF LENGTH