

## Silicon Carbide Thyristor

$V_{FBM}$	=	6500 V
$I_{T(AVM)}$	=	60 A
$Q_{rr}$	=	2.95 $\mu$ C


### Features

- 6500 V Asymmetric SiC NPNP Thyristor
- 150 °C operating temperature
- Robust compact fully soldered package
- SOT-227 (ISOTOP) base plate form factor
- Fast turn on characteristics
- Lowest in class  $Q_{rr}/I_{T(AVM)}$

### Applications

- Grid Tied Solar Inverters
- Wind Power Inverters
- HVDC Power Conversion
- Utility Scale Power Conversion
- Trigger Circuits/Ignition Circuits

### Package



### Maximum Ratings

Parameter	Symbol	Conditions	Values	Unit
Repetitive peak forward voltage	$V_{FBM}$	$T_j = 25\text{ }^\circ\text{C}$	6500	V
Repetitive peak reverse voltage	$V_{RBM}$	$T_j = 25\text{ }^\circ\text{C}$	50	V
Maximum average on-state current	$I_{T(AVM)}$	$T_c \leq 120\text{ }^\circ\text{C}$	60	A
RMS on-state current	$I_{T(RMS)}$	$T_c \leq 120\text{ }^\circ\text{C}$	104	A
Non-repetitive peak on-state current	$I_{T,max}$	$T_c = 25\text{ }^\circ\text{C}$ , $t_p = 2\text{ }\mu\text{s}$ , $D = 0.1$	tdb	A
Power dissipation	$P_{tot}$	$T_c = 25\text{ }^\circ\text{C}$	919	W
Operating and storage temperature	$T_j, T_{stg}$		-55 to 150	$^\circ\text{C}$

### Electrical Characteristics

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Maximum peak on state voltage	$V_{KA(ON)}$	$I_k = -60\text{ A}$ , $T_j = 25\text{ }^\circ\text{C}$ $I_k = -60\text{ A}$ , $T_j = 150\text{ }^\circ\text{C}$		-3.90 -3.70		V
Anode-cathode threshold voltage	$V_{KA(TO)}$	$T_j = 25\text{ }^\circ\text{C}$ (150 °C)		-3.1(-2.8)		V
Anode-cathode slope resistance	$R_{AK}$	$T_j = 25\text{ }^\circ\text{C}$ (150 °C), $I_k = -60\text{ A}$		9.4(9.5)		m $\Omega$
Leakage current	$I_L$	$V_{KA} = -6500\text{ V}$ , $V_{GA} = 0\text{ V}$ , $T_j = 25\text{ }^\circ\text{C}$ $V_{KA} = -6500\text{ V}$ , $V_{GA} = 0\text{ V}$ , $T_j = 150\text{ }^\circ\text{C}$		20 50		$\mu$ A
Gate trigger current	$I_{GT}$	$T_j = 25\text{ }^\circ\text{C}$ , $t_p = 10\text{ }\mu\text{s}$		-100		mA
Holding current	$I_H$	$T_j = 25\text{ }^\circ\text{C}$		tdb		mA
Rise time	$t_R$	$I_G = -3\text{ A}$ , $V_{KA} = -2200\text{ V}$		170		ns
Delay time	$t_D$	$I_k = -60\text{ A}$ , $T_j = 25\text{ }^\circ\text{C}$		45		ns
Reverse recovery charge	$Q_{rr}$			2.95		$\mu$ C
Recovered charge, 50% chord	$Q_{ra}$	$di/dt = 360\text{ A}/\mu\text{s}$ , $I_k = -60\text{ A}$ , $V_{KA} = 20\text{ V}$		1.6		$\mu$ C
Reverse recovery current	$I_{rm}$	$dV/dt(\text{re-app}) = -362\text{ V}/\mu\text{s}$ , $T_j = 25\text{ }^\circ\text{C}$		15		A
Circuit commutated turn-off time	$t_q$			6.7		$\mu\text{s}$

### Thermal Characteristics

Thermal resistance, junction - case	$R_{thJC}$	0.136	$^\circ\text{C}/\text{W}$
-------------------------------------	------------	-------	---------------------------

### Mechanical Properties

Mounting torque for base	$M_b$	Heat sink surface must be optically flat	1.5	Nm
Mounting torque for top	$M_t$		1.3	Nm
Weight	$W_t$		30	g

1. Considering worst case  $Z_{th}$  conditions




Figure 1: Typical On State Characteristics




Figure 2: Typical Forward Blocking Characteristics




Figure 3: Typical Current Derating Curves ( $D = t_p/T, t_p = 400 \mu s^1$ )




Figure 4: Typical Current Rating versus Pulse Duration Curves at  $T_c = 120 \text{ }^\circ\text{C}$




Figure 5: Typical Turn On Characteristics at 25 °C




Figure 6: Typical Turn Off Characteristics at 25 °C




Figure 7: Typical Reverse Recovery Characteristics at 25 °C




Figure 8: Typical Transient Thermal Impedance

**Revision History**

Date	Revision	Comments	Supersedes
2010/11/10	1	First generation release	

Published by  
GeneSiC Semiconductor, Inc.  
43670 Trade Center Place Suite 155  
Dulles, VA 20166

GeneSiC Semiconductor, Inc. reserves right to make changes to the product specifications and data in this document without notice.

GeneSiC disclaims all and any warranty and liability arising out of use or application of any product. No license, express or implied to any intellectual property rights is granted by this document.

Unless otherwise expressly indicated, GeneSiC products are not designed, tested or authorized for use in life-saving, medical, aircraft navigation, communication, air traffic control and weapons systems, nor in applications where their failure may result in death, personal injury and/or property damage.