



PART NO.			"L"
#4-40 THREAD	#6-32 THREAD	#8-32 THREAD	
MFTS4-4-48	MFTS6-4-48*	MFTS8-4-48*	1/4 (6.4)
MFTS4-5-48	MFTS6-5-48	MFTS8-5-48**	5/16 (7.9)
MFTS4-6-48	MFTS6-6-48	MFTS8-6-48**	3/8 (9.5)
MFTS4-7-48	MFTS6-7-48	MFTS8-7-48	7/16 (11.1)
MFTS4-8-48	MFTS6-8-48	MFTS8-8-48	1/2 (12.7)
MFTS4-9-48	MFTS6-9-48	MFTS8-9-48	9/16 (14.3)
MFTS4-10-48	MFTS6-10-48	MFTS8-10-48	5/8 (15.9)
MFTS4-11-48	MFTS6-11-48	MFTS8-11-48	11/16 (17.5)
MFTS4-12-48	MFTS6-12-48	MFTS8-12-48	3/4 (19.1)
MFTS4-13-48	MFTS6-13-48	MFTS8-13-48	13/16 (20.6)
MFTS4-14-48	MFTS6-14-48	MFTS8-14-48	7/8 (22.2)
MFTS4-16-48	MFTS6-16-48	MFTS8-16-48	1.00 (25.4)
MFTS4-18-48	MFTS6-18-48	MFTS8-18-48	1-1/8 (28.6)
MFTS4-20-48	MFTS6-20-48	MFTS8-20-48	1-1/4 (31.8)
MFTS4-22-48	MFTS6-22-48	MFTS8-22-48	1-3/8 (34.9)

THREAD SIZE	DIM "A"	DIM "B" MIN.
#4-40	3/16 (4.8)	3/16 (4.8)
#6-32	1/4 (6.4)	1/4 (6.4)
#8-32	3/8 (9.5)	3/8 (9.5)

* DIM. "B" IS 3/16 (4.8) MIN.
 ** DIM. "B" IS 1/4 (6.4) MIN.

NOTES:

- MATERIAL: NYLON 6/6 (RMS-48);
 FLAME RETARDANT, NYLON UL-94 V0, (RMS-103),
 AVAILABLE BY SPECIAL ORDER ONLY.
- COLOR: NATURAL.

TITLE: MALE-FEMALE THREADED STANDOFFS					DWG IN IN (MM)		
TOLERANCES UNLESS NOTED .XX=±.010 .XXX=±.005 FRAC=±1/64 ANG=±1°			FILE # MFTS MAT'L: SEE NOTES RE: RICHCO, INC.	DWN: J.B. DT: 01-20-97	APP: DT: RICHCO INC. PO BOX 804238, CHICAGO, 60680 (773) 539-4060	FINAL PART # SEE TABLE	PRINT TYPE CA
D	CHANGED FILE NUMBER	SM 05.11.01					
C	MAT'L RMS-103 WAS RMS-19	J.L.07.05.00					
B	MAT'L RMS-19 ADDED	J.L. 8.16.99					
A	"B" DIM CHANGED ON SMALL PARTS	JB 07.15.97					
REV	DESCRIPTION	ENGR DATE					