


示意图 SCHEMATIC



安装孔 PIERCING PLAN

规格 Specifications

额定负荷 Ratings	DC 30 V 100mA
初始接触电阻 Initial Contact Resistance	200 m $\Omega$ Max.
绝缘电阻 Insulation Resistance	DC250 V.60 Sec. 10 M $\Omega$ Min.
抗电强度 Dielectric Voltage	AC 250 V(50~60HZ) 60 Sec.
操作力 Operationg Force(gf)	30 $\pm$ 20 gf
自由位置 Free Position	5.20mm Max
动作位置 Operationg Position	3.20 $\pm$ 0.40mm
超行程 Over Travel	2.00 $\pm$ 0.40mm
负荷寿命 Operationg Life With Load	20,000 Cycles

序NO.	零件 PART	材料 MATERIAL	数量 QTY	备注 REMARKS	标号 REV	内容 DESCRIPTION	签名 SIGN.	日期 DATE
7	端子 TERMINAL	C2680R (b)	3	Ag PLATED				
6	胶壳 HOUSING	PA46 (b)	1	BLACK C	A03	零件材料标示变更见 (b)	曹文斌	2006-03-20
5	弹簧 SPRING (b)	SUS	1	NATURAL		机械寿命变更为负荷寿命见 (b)		
4	接触片 CONTACT CLIP (b)	C5210R	1	Ag CLAD		追加零件标示见 (b)		
3	滑块 SLIDER (b)	PBT	1	BLACK C	A02	PA 1300G011 变更为 PA46 TE250F6-BK 见 (c)	曹文斌	2006-01-21
2	胶盖 COVER	PA46 (b)	1	BLACK C		3.30 变更为 3.70 见 (c)		
1	胶柄 KNOB	POM (b)	1	BLACK C	A01		曹文斌	2005-12-30
					标号 REV	内容 DESCRIPTION	签名 SIGN.	日期 DATE
					DWG NO. ITEM2383			

TOLERANCES UNLESS OTHERWISE SPEC.		TITLE	DETECTOR SWITCH		ITEM NO	DS-080-C PA		
UNDER 1	$\pm 0.10$	DRAWN	曹文斌	2006-03-20	VERSION	A03	PAGE	1 OF 1
1 - 10	$\pm 0.30$	REVIEWED	张念明	2006-03-20	SCALE	NO SCALE	UNIT	mm
OVER 10	$\pm 0.50$	APPROVED	林高全	2006-03-21	PROJECTION			

**COMAX** ELECTRONICS (HUIZHOU) CO.,LTD.