

# Low Pass Filter

## VLF-5500+

50Ω \*DC to 5500 MHz



CASE STYLE: FF704

Connectors	Model
SMA	VLF-5500+

### Maximum Ratings

Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C
RF Power Input*	8W at 25°C
DC Current Input to Output	0.5A max. at 25°C

\*Passband rating, derate linearly to 3 W at 100°C ambient  
Permanent damage may occur if any of these limits are exceeded.

### Features


- Rugged uni-body construction, small size
- 7 sections
- Excellent power handling, 8W
- Temperature stable
- Low cost
- Protected by US Patent 6,943,646

### Applications

- Harmonic rejection
- Transmitters/receivers
- Lab use

**+RoHS Compliant**  
The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

### Outline Drawing



### Outline Dimensions (inch/mm)


B	D	E	wt.
.410	1.43	.312	grams
10.41	36.32	7.92	10

### Low Pass Filter Electrical Specifications (T<sub>AMB</sub> = 25°C)


PASSBAND (MHz) (loss < 2 dB) Max.	f <sub>co</sub> , MHz Nom. (loss 3 dB) Typ.	STOP BAND (MHz) (loss, dB)			VSWR (:1)		NO. OF SECTIONS
		F 20 Min.	30 Typ.	FR 20 Typ.	Stopband Typ.	Passband Typ.	
*DC - 5500	6200	7200	6770 - 9500	12100	17	1.3	7

\* Not for use with DC voltage at input and output ports

### Typical frequency response




### Electrical schematic




### Typical Performance Data at 25°C

Frequency (MHz)	Insertion Loss (dB)	VSWR (:1)
40	0.04	1.04
500	0.12	1.04
1500	0.20	1.14
3000	0.39	1.33
4800	0.51	1.13
5500	0.81	1.37
6200	2.80	1.99
6300	4.85	3.30
6400	8.25	5.72
6550	15.66	10.96
6700	26.89	15.96
6770	34.76	17.75
7200	26.40	24.48
9500	40.75	37.77
10500	51.98	48.26
12100	32.16	64.35
15000	25.07	37.77

VLF-5500+  
INSERTION LOSS



VLF-5500+  
VSWR



### Notes

- Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at [www.minicircuits.com/MCLStore/terms.jsp](http://www.minicircuits.com/MCLStore/terms.jsp)

