

Specification Sheet

Part Number: 150-74890



Fir tree design can be used with a wide variety of applications.

Disc' on the top of the fir tree covers the hole and minimizes the ingress of water and dirt.

Friction tab inside of fir tree allows tie to sit in mount without falling out prior to installation.

2-Piece Cable Tie/Fir Tree Mount, 6.0" Long, Mounting Hole Diameter 0.23" - 0.24", PA66HS, Black, 500/pkg

Article Number 150-74890

Type T30RFT6D10

Color Black (BK)

Quantity Per bag

Product Description HellermannTyton's fir tree mounts provide a secure grip in a mounting hole and protect against dirt and other impurities. The mount can slide along the strap of the cable tie for proper orientation. The fir tree mounts are designed to provide a low insertion force and high extraction force. This mount is sold as an assembly with the cable tie.

Short Description 2-Piece Cable Tie/Fir Tree Mount, 6.0" Long, Mounting Hole Diameter 0.23" - 0.24", PA66HS, Black, 500/pkg

Global Part Name T30RFT6D10-PA66HS/PA66HIRHS-BK

Minimum Tensile Strength (Imperial)	30.0
Minimum Tensile Strength (Metric)	135
Length L (Imperial)	6.0
Length L (Metric)	150
Fixation Method	Fir Tree
Identification Plate Position	none
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.14
Width W (Metric)	3.5
Bundle Diameter Min (Imperial)	0.06
Bundle Diameter Max (Imperial)	1.2
Bundle Diameter Max (Metric)	32.0
Height H (Imperial)	0.04
Height H (Metric)	1.1
Panel Thickness Min (Imperial)	0.03

Panel Thickness Max (Imperial)	0.12
Panel Thickness Min (Metric)	0.8
Panel Thickness Max (Metric)	4.3
Mounting Hole Diameter D (Imperial)	0.23 - 0.24
Mounting Hole Diameter D (Metric)	5.8 - 6.2 mm
Mounting Hole Diameter D Min (Imperial)	0.25
Mounting Hole Diameter D Max (Imperial)	0.27
Mounting Hole Diameter D Max (Metric)	6.2
Disc Diameter (Metric)	9.8
Disc Diameter (Imperial)	0.63
Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HIRHS PA66HS
Material Cable Tie	Polyamide 6.6 heat stabilized (PA66HS)
Flammability	UL 94 HB
UV Resistant (Yes/No)	No

Operating Temperature -40°F to +221°F (-40°C to +105°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 500

Package Quantity (Metric) 500

Customs Number 3926909988

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)