



Note 1 After the vertical mating of the adapter (MS-156-HRMJ-29) and the receptacle (MS-156C) is completed, adjust the fixture stop and the load force to within 6 to 10N.  
 Note 2 No obstacles in this area to avoid the interference when floating.

NO.	MATERIAL	FINISH	REMARKS	NO.	MATERIAL	FINISH	REMARKS
1	BERYLLIUM COPPER	GOLD PLATING		8	PTFE		
2	BERYLLIUM COPPER	NICKEL PLATING		9	STAINLESS STEEL		
3	BERYLLIUM COPPER	GOLD PLATING		10	POLYACETAL		
4	BERYLLIUM COPPER	GOLD PLATING		11	POLYACETAL		
5	BERYLLIUM COPPER	GOLD PLATING		12	STAINLESS STEEL		
6	PTFE			13	STAINLESS STEEL		GOLD PLATING
7	PTFE			14	STAINLESS STEEL		

UNITS	SCALE	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	4 : 1					

APPROVED : KY. SHIMIZU	10.02.02	DRAWING NO.	EDC3-180963-00
CHECKED : TY. OZAKI	10.01.29	PART NO.	MS-156-HRMJ-29
DESIGNED : TO. KATAYAMA	10.01.29	CODE NO.	CL358-0295-8-00
DRAWN : TO. KATAYAMA	10.01.29	NO.	1