



**NOTES:**

1. METALSHELLS: STEEL; min. 315µin TIN over 40-80µin NICKEL
2. INSULATORS: PBT GF UL 94 V-0; GREEN
3. SIGNAL CONTACTS: COPPER ALLOY  
PLATING: GOLD FLASH over NICKEL  
SOLDER CUP ACCEPTS CABLE AWG 20
4. NO CONTACTS ON POS. A1 - A6
5. CONNECTOR IS PART MARKED: 3013W6SAM99A10X CONEC ABC

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND					tolerance	dim. in mm	scale:	2:1 (5:1)		
					date		name	material:	see notes	
					drawn	29.10.14	Henneboel	title: <b>D-SUB COMBINATON FEMALE</b> 13W6S		
					appd.	29.10.14	Schmidt			
					norm					
					d-old			dwg no:		
					a	Original			13K1A4798 DIN-A3 sh: 1	
				rev.	description	date	name			
								part no:	3013W6SAM99A10X	