## GS4MT Hand Operated Installation Tool

- Single handle operation for fast installation
- Cable tie side entry for immediate positioning of tie and tool
- Controlled tension, fully adjustable
- Easy removal of excess tie

- Qualified product listed per MIL Standard MS90387-3
- Automatically tensions and cuts off tie when predetermined tension is reached
- Installs standard .18 inch (4.6mm), light-heavy .25 inch (6.4mm) and heavy .31 inch (7.9mm) cross section ties



**GS4MT**

| Part Number | Part Description | Std. Pkg. Qty. |
|---|---|---|
| GS4MT | Used with standard, light-heavy, and heavy cross section Pan-Steel® type MLT ties, type MLTC/MLTFC coated ties, and type MLTDH double wrapped ties. | 1 |
| K4M-BLD | Replacement cutter blade for GS4MT. | 1 |
| K4MTG | Replacement tension gripper for GS4MT. | 1 |
| CAMT | Cut-off accessory. Use this accessory with GS4MT tool to cut MBH or MBS continuous banding. Accessory drops in place for use. | 1 |



**Side Entry**



**CAMT**

## Tool Tension Locking Kits

- For applications requiring a locking device on either the selector knob (one cross section size and tension only) or tension level adjustment (but allow cross section size changes)



To lock selector knob and tension level.



To lock fine adjustment.

| Part Number | Part Description | Std. Pkg. Qty. |
|---|---|---|
| TTLK3 | Tool tension locking kit for GS4MT and PPTMT installation tools. | 1 |