

Specification Sheet

Part Number: 558-00057



Article Number

558-00057

Type

TAG85-100W444SM

Color

White (WH)

Features & Benefits

- HellermannTyton SwiftMark Self-Laminating Labels come on rolls for convenient loading and printing.
- Labels are conformable so that they can bend around small gauge wires and tight bends without coming loose over time.
- Labels are UL recognized for indoor and outdoor use to expand application options.
- HellermannTyton SwiftMark Self-Laminating labels are designed for high speed printing and dispensing to work flawlessly in the SwiftMark applicator and printer.

Quantity Per

reel

Product Description

HellermannTyton's self-laminating labels are designed for use in the SwiftMark automatic label applicator and printer. Manufactured in a conformable frosty clear vinyl with good contrast clarity, they are designed with a clear overlap to protect the printed text. The labels come 1 across on a spindle that fits into the applicator. Labels are designed with a special adhesive that bonds quickly to wire and cable using a custom high speed dispensing liner. The printed labels can be used on wires as small as .06" (1.52mm) in diameter and as large as .75" (19mm) in diameter. A UL recognized mark for indoor and outdoor use can be achieved using the TT100 series ribbon (part no. 556-00165). SwiftMark vinyl label meet all the requirements of UL969 - STANDARD FOR MARKING AND LABELING SYSTEMS edition -4. Labels UL recognized under UL file number MH18396. The SwiftMark can accept labels widths that range from .5" (12.7mm) to 2.0" (50.8mm).

Short Description

SwiftMark Self-Laminating Label, 1.75" x 1.0" x 3.0", VL, White, 1000/roll

Global Part Name

TAG85-100W444SM-100B-WH

Technical Description

SwiftMark Self-Laminating Label, 1.75" X 1.0" X 3.0", White

Variant

Roller form

Width W (Imperial)

1.75

Width W (Metric)

44.45

Bundle Diameter Min (Imperial)

.14

Bundle Diameter Min (Metric)

3.50

Bundle Diameter Max (Imperial)

.29

Bundle Diameter Max (Metric)

7.60

Thickness T (Metric)

35

Height H (Imperial)

.50

Height H (Metric) 12.70

Width of Liner (Metric) 47.62

Width of Liner (imperial) 1.875

Outside Diameter Max(Imperial) 0.39

Outside Diameter Min (metric) 10.1

Outside Diameter Min(Imperial) 0.79

Outside Diameter Max (metric) 20.2

Material Type 100B, Vinyl (PVC), white transparent (WH/CL), self laminating

Material Shortcut 100B

Adhesive Acrylic

Adhesive Operating Temperature -40°F to +194°F (-40°C to +90°C)

Operating Temperature (Metric) -40°F to +176°F (-40°C to +80°C)

ROHS Complaint Yes

Certification/Specification WEB UL-Recognized

UL Recognized (US) Yes

Package Quantity(Imperial)	1000
Package Quantity (Metric)	1000
Customs Number	3919102055
Labels per Row	1
Weight (Metric)	1.1
Weight (Imperial)	2.42