





UNIT:mm


10000±100mm



HDMI 19P/M MOLDING TYPE
 INNER MOLD NO.:HJ-CT-091
 OUTER MOLD NO.:HJ-CT-092/093
 (MOULD NO.)

HDMI 19P/M MOLDING TYPE
 INNER MOLD NO.:HJ-CT-091
 OUTER MOLD NO.:HJ-CT-092/093
 (MOULD NO.)

PIN ASSIGNMENT



- ELECTRICAL TEST
1. 100% open short & miss wire test
2. Insulation resistance: DC/300V 5Mohm(Min)
3. Contactor resistance: ≤3ohm Max
- 2.HDTV-DVD TEST:1080P (高清电视测试 : 1080P)
- 3.RoHS compliant

NO.	NAME	Q'TY	SPECIFICATION
①	CABLE	1	28#1/0.32BC+FPPE ID0.95*1P+D 1/0.32BC+HDPE ID0.6+AL]*4P+(1/0.32BC+HDPE ID0.70)*1P+(1/0.32BC+HDPE ID0.70)*5C+AL+D 1/0.32BC+R 28#/0.12ALMG+PVC BLACK OD7.3MM
②	TUBE	10	HEAT SHRINK TUBE BLACK ODO.8*L=9mm.
③	TUBE	10	HEAT SHRINK TUBE CLEAR ODO.8*L=6mm.
④	TUBE	2	HEAT SHRINK TUBE CLEAR ODO.8*L=20mm.
⑤	CONN	2	HDMI 19P/M SOLDER STYLE SHORT BODY PIN 3U" SHELL-PLATED GOLD INSULATION BLACK
⑥	IN JACKET	8g	INNER MOLD: CLEAR LDPE
⑦	OUT JACKET	16g	OUTER MOLD: 45P PVC COLOR: BLACK

CNC Tech, LLC Industrial Cable and Connector Technology			
DRAWN BY	Zhonghs	DRAWING NO.	VG/LJQ-094-001
CHECKED BY		CUSTOMER	CNC
APPROVAL BY		ITEM NO.	740-10010-01000
DECIDE BY		DATE	2012-02-14
VERSIONS/EDITION	A/0	PROJECTION	