

Terminal housing f. motor Han 10B 1 leve



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 09 30 410 0974 |
| Specification | Terminal housing f. motor Han 10B 1 leve |
| HARTING eCatalogue | https://b2b.harting.com/09304100974 |

Identification

| | |
|-----------------------------|-------------------------------|
| Category | Hoods/Housings |
| Series of hoods/housings | Han-Drive® |
| Type of hood/housing | Housing for motor application |
| Description of hood/housing | With thermo-plastic cover |

Version

| | |
|----------------|----------------------|
| Size | 10 B |
| Locking type | Single locking lever |
| Han-Easy Lock® | Yes |

Technical characteristics

| | |
|--|--|
| Limiting temperature | -40 ... +125 °C |
| Note on the limiting temperature | For use as a connector according to IEC 61984. |
| Degree of protection acc. to IEC 60529 | IP65 |
| Type rating acc. to UL 50 / UL 50E | 4 4X 12 |
| Distance assembly fixing holes | 70 mm |

Material properties

| | |
|-------------------------|--------------------|
| Material (hood/housing) | Aluminium die-cast |
| Surface (hood/housing) | Uncoated |
| Material (seal) | NBR |



Pushing Performance
 Since 1945

Material properties

| | |
|--|---|
| Material (locking) | Polycarbonate (PC) Stainless steel |
| Colour (locking) | RAL 7037 (dust grey) |
| Material flammability class acc. to UL 94 (locking levers) | V-0 |
| RoHS | compliant with exemption |
| RoHS exemptions | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status | compliant with exemption |
| China RoHS | 50 |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Yes |
| REACH SVHC substances | 6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol Potassium 1,1,2,2,3,3,4,4,4-nonafluorobutane-1-sulphonate Lead |
| ECHA SCIP number | d6e3a86d-3ff8-4b1f-8b90-52bbe4922dab |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Lead Nickel Naphthalene |
| Fire protection on railway vehicles | EN 45545-2 (2020-08) |
| Requirement set with Hazard Levels | R22 (HL 1-3) R23 (HL 1-3) |

Specifications and approvals

| | |
|-----------|--------|
| CE | Yes |
| Approvals | DNV GL |

Commercial data

| | |
|--------------------------------|--|
| Packaging size | 1 |
| Net weight | 291.4 g |
| Country of origin | Germany |
| European customs tariff number | 85389099 |
| GTIN | 5713140170926 |
| eCl@ss | 27440202 Shell for industrial connectors |