

## FO connecting cable - FOC-PN-B-1000/M12-C/SCRJ/1 - 1408865

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Assembled FO cable, round cable, 980/1000 µm POF fiber, M12 fiber optic connector to SC-RJ/IP20

POF cable, assembled with M12 connector to SC-RJ

### Product Description

POF cable, assembled with M12 connector to SC-RJ

### Why buy this product

- 2.2 mm individual wires made from extremely hard-wearing polyamide (PA)
- Assembled patch cable with test report
- M12-OPTIC with recessed ferrules to protect against damage
- optimized polishing for even better attenuation values
- Rugged polyurethane (PUR) outer sheath
- Highly tear-resistant aramid strain relief elements
- Pin connector pattern in accordance with DIN/IEC 61754-27
- Included in PROFINET planning guideline (v1.14)
- Robust connector, IP65/IP67
- Can be used in 10/100/1000 Mbps Ethernet systems
- Halogen-free, ozone, and UV resistant



Ethernet

### Key Commercial Data

Packing unit	1 STK
Custom tariff number	85447000
Country of origin	Germany

# FO connecting cable - FOC-PN-B-1000/M12-C/SCRJ/1 - 1408865


## Technical data

### Standards and Regulations

Impact strength	2 Nm / 10 x
Flammability rating according to UL 94	V0

## Drawings

Dimensional drawing



## Classifications

### eCl@ss

eCl@ss 5.1	27061003
eCl@ss 8.0	27061003
eCl@ss 9.0	27061003

### ETIM

ETIM 4.0	EC001263
ETIM 5.0	EC001263

## Approvals

### Approvals

---

Approvals

EAC

---

Ex Approvals

---

Approvals submitted

---

## FO connecting cable - FOC-PN-B-1000/M12-C/SCRJ/1 - 1408865

### Approvals

#### Approval details

EAC
-----

### Accessories

#### Accessories

##### Circular connectors (device side)

FO transceiver - FOC-M12-MNNA-TC-650 - 1416716



M12 FO transceiver, duplex, wavelength: 650 nm for 125 Mbps, for POF and PCF fiber, for PCB mounting, M16 fastening thread, with sealing cap, including I<sup>2</sup>C interface for transceiver monitoring and management

Fiber optic coupling - FOC-M12-BU/BU - 1416677



Fiber optics coupling M12, duplex, suitable for all fibers, with wall bracket, IP65 degree of protection

Fiber optic contact insert - FOC-M12-RS-POF - 1406421



Replacement ferrule set (10 pcs.) for M12 POF fiber optic connector (Order No. 1416606)

### Spare parts

Fiber optic contact insert - FOC-M12-RS-POF - 1406421



Replacement ferrule set (10 pcs.) for M12 POF fiber optic connector (Order No. 1416606)

