

#### **RONDA-ZT45-C**

Double asymmetric beam for wall-washing and aisle lighting with holder C compatible with LEDIL HEKLA

#### **SPECIFICATION:**

Dimensions Ø 53.9 mm
Height 16.6 mm
Fastening socket
ROHS compliant yes ①



#### **MATERIALS:**

Component	Type	Material	Colour	Finish
F15159_RONDA-ZT45	Single lens	PMMA	clear	
F15635_RONDA-HLD-C	Holder	PC	white	

#### **ORDERING INFORMATION:**

#### **Quantities for one set:**

Single lens 1 Holder 1




# PRODUCT DATASHEET RONDA-ZT45-C

Component		Qty in box	MOQ	MPQ	Box weight (kg)
F15159_RONDA-ZT45  » Box size: 480 x 280 x 300 mm	Single lens	420	120	30	6.5
F15635_RONDA-HLD-C  » Box size: 480 x 280 x 300 mm	Holder	420	120	30	4.1




# PRODUCT DATASHEET RONDA-ZT45-C




See also our general installation guide: <a href="www.ledil.com/installation\_guide">www.ledil.com/installation\_guide</a>

3/19

















# **CITIZEN**

CLL02x/CLU02x (LES10)

 $\mathsf{FWHM}\,/\,\mathsf{FWTM}$ Asymmetric Efficiency 88 % Peak intensity 0.6 cd/lm LEDs/each optic Light colour White Required components:


F15255\_HEKLA-SOCKET-C



# **CITIZEN**

LED CLL03x/CLU03x FWHM / FWTM Asymmetric Efficiency 82 % Peak intensity 0.4 cd/lm LEDs/each optic 1 White Light colour

F15859\_HEKLA-SOCKET-I




Required components:

LED CLU700/701/702/703

FWHM / FWTM Asymmetric Efficiency 90 % Peak intensity 0.8 cd/lm LEDs/each optic Light colour White Required components:

F15255\_HEKLA-SOCKET-C




# **CITIZEN**


CLU7A2/7A3 FWHM / FWTM Asymmetric Efficiency 91 % Peak intensity 1 cd/lm

LEDs/each optic White Light colour Required components:


F15255\_HEKLA-SOCKET-C

































Fortimo SLM L13 CoB

FWHM / FWTM Asymmetric Efficiency 83 % Peak intensity 0.4 cd/lm LEDs/each optic Light colour White Required components:


C16142\_HEKLA-SOCKET-K Bender Wirth: 432 Typ L8



LED LC003D / LC006D / LC009D / LC013D

FWHM / FWTM Asymmetric Efficiency 89 % Peak intensity 0.6 cd/lm LEDs/each optic 1 White Light colour Required components:

F15255\_HEKLA-SOCKET-C




# SAMSUNG

LC010C FWHM / FWTM Asymmetric Efficiency 89 % Peak intensity 0.7 cd/lm

LEDs/each optic Light colour White Required components:

F15848\_HEKLA-SOCKET-G



# SAMSUNG


LC010C G2 FWHM / FWTM Asymmetric Efficiency 89 %

Peak intensity 0.9 cd/lm LEDs/each optic

White

Light colour Required components: F15255\_HEKLA-SOCKET-C










LED MJT COB LES 9.8

FWHM / FWTM Asymmetric Efficiency 87 % Peak intensity 0.5 cd/lm LEDs/each optic

Light colour White Required components:

F15255\_HEKLA-SOCKET-C




# **TRIDONIC**

LED SLE G7 LES09

FWHM / FWTM Asymmetric Efficiency 89 % Peak intensity 0.6 cd/lm LEDs/each optic 1

White Light colour Required components:

F15255\_HEKLA-SOCKET-C




#### TRIDONIC

SLE G7 LES13

FWHM / FWTM Asymmetric Efficiency 85 % Peak intensity 0.4 cd/lm

LEDs/each optic Light colour White Required components:

F15859\_HEKLA-SOCKET-I




# **XICATO**

XOB 14.5 mm


FWHM / FWTM Asymmetric Efficiency 83 % Peak intensity 0.4 cd/lm LEDs/each optic White Light colour

F15859\_HEKLA-SOCKET-I

Required components:










#### **OPTICAL RESULTS (SIMULATED):**



LED VERO10 FWHM / FWTM Asymmetric

Efficiency %
LEDs/each optic 1
Light colour White

Required components: F15616\_HEKLA-SOCKET-F




# **WNICHIA**

LED COB T-Type
FWHM / FWTM Asymmetric
Efficiency 84 %
Peak intensity 0.8 cd/lm
LEDs/each optic 1
Light colour White

Required components:

F15848\_HEKLA-SOCKET-G





# PRODUCT DATASHEET RONDA-ZT45-C

#### **GENERAL INFORMATION:**

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

Due to use of high power COB's with this product, special attention to proper thermal design is highly recommended. LEDiL has no liability for direct, indirect or consecutive damages arising from the LEDiL products being used outside of the recommended temperature range.

#### **MATERIALS:**

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

#### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### **LEDIL Oy**

Joensuunkatu 13 FI-24240 SALO Finland

#### LEDiL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

# Ledil Optics Technology (Shenzhen) Co., Ltd.

# 405 , Block B Casic Motor Building Shenzhen 518057 P.R.CHINA

# Local sales and technical support

www.ledil.com/ where\_to\_buy

#### **Shipping locations**

Salo, Finland Hong Kong, China

#### **Distribution Partners**

19/19

www.ledil.com/ where\_to\_buy