



**DC POWER CONNECTORS: KLDLX Series**  
Right Angle Panel Mount DC Power Jack

**Product Features**

- 2.0mm and 2.5mm Pin Options
- Panel Mount
- Solder Eyelets
- Built in DC On/Off Switch
- Full metal shell for increased strength
- Locks when used with the KLDLX-P Series

**Performance Specifications**

**Materials and Finish**

- Housing:** PBT Thermoplastic, UL94V-0 Rated, Black Color
- Center Pin & Threaded Barrel:** Brass, Nickel Plated
- Contact #1, #3:** Brass, Tin Plated
- Contact #2:** Phosphor Bronze, Tin Plated
- Nut:** Brass, Nickel Plated
- Washer:** SPCC, Nickel Plated

**Electrical Characteristics**

- Rated Current:** 5A
- Rated Voltage:** 24V DC
- Insulation Resistance:** 100 Megohms Min. at 500V DC
- Contact Resistance:** 30 milliohms Max.
- Dielectric Withstanding Voltage:** 500V AC Min. for 1 Minute
- Recommended Minimum Panel Thickness:** 1.5mm


**Mechanical Characteristics**

- Durability Test:** 5000 Cycles
- Insertion Force:** 3.0kg Max.
- Extraction Force:** 0.3kg Min.


Generated Part Number

KLDLX-202-B

Part Number Builder



**Series**

KLDLX - Panel Mount DC Power Jack

**Product Type**

0202 - Closed body, 2mm options

**Diameter**

- 2.0mm Center Pin Diameter
- 2.5mm Center Pin Diameter

**Barrel length**

- 5.7mm barrel length
- LB - 8.0mm barrel length (Contact Kycon for more Information)

Contact Kycon For Other Options

**KLDLX Series**

Dimensions in mm

