

0.75 METER LENGTH




Connector A
112234
BNC Jack Straight
Bulkhead - Rear Mount Brass Nickel

50 Ohm RG-174
Continuity/Hi-Pot

Connector B
122454
TNC Jack Right Angle
Bulkhead - Rear Mount Brass Nickel + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink
Assembly shall be built with SN96.5 LEAD FREE solder.
See Routing Notes for additional assembly & testing instructions.



Connector A	Cable	Connector B
<p>Part #: 112234 Description: BNC Clamp BHD JK RG188 500 Type: BNC Gender: Jack Body Type: Straight Contact Type: Crimp Polarity: Standard Impedance: 50 Ohm Mounting: Bulkhead - Rear Mount Body Material: Brass Body Finish: Nickel IP Rating: None Contact Material: Beryllium Copper Contact Finish: Silver Max. Freq.: 4 GHz Booting: BNC Jack Straight BHD</p>	<p>Part #: RG-174 Description: RG-174 - PE 0.1 Dielectric: PE Shielding: Braid Diameter: 0.1 Impedance: 50 Ohm Sheathing: None Testing: Continuity Hi-Pot Length: 0.75 Meter</p>	<p>Part #: 122454 Description: TNC R/A BHD JK RG174 RG316 LMR100 500 Type: TNC Gender: Jack Body Type: Right Angle Contact Type: Solder Polarity: Standard Impedance: 50 Ohm Mounting: Bulkhead - Rear Mount Body Material: Brass Body Finish: Nickel IP Rating: None Contact Material: Phosphor Bronze Contact Finish: Gold Max. Freq.: 11 GHz Booting: TNC Jack Right Angle Clocking: 0°</p>



CONTROLLED DOCUMENT - DO NOT COPY

THIS DRAWING MAY CONTAIN PATENTED OR PROPRIETARY INFORMATION AND MUST NOT BE USED FOR ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE INC. IT MAY NOT BE REPRODUCED OR TRANSCRIBED IN ANY FORM WITHOUT THE WRITTEN CONSENT OF CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.

Title:
BNC-ST-JK/TNC-RA-JK G174 0.75M

Part No:
Q-040480003.75M

UNLESS SPECIFIED
TOLERANCE:
0-18 inches +/- 1/2"
over 18" +/- 2%
ASSEMBLY:
CENTER LABEL IF LENGTH
IS LESS THAN 12 INCHES