

MICRO SWITCH

FREEPORT ILLINOIS, U.S.A.
A DIVISION OF HONEYWELL
FED. MFG. CODE 91929

SWITCH-BASIC

CATALOG LISTING
V3L-3288

CQ-X2760

S

V3L-3288

M

DRAWING
NUMBER

8

ISSUE
84

REPLACES

RELEASE NO. PR-14942

CHECK

CHECK

3/2


4 AUG 86

CHECK

1 AUG 86

DRAWN

LJF




NOTES

- 1 - (3) VP-10320 SCREWS AND (3) VP-14672 WASHERS
FURNISHED UNASSEMBLED IN BULK

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

THIRD ANGLE PROJECTION



CHARACTERISTICS

OPERATING FORCE-----88 GRAM MAX
RELEASE TRAVEL----- .017 MIN
RELEASE FORCE----- 6 GRAM MIN
DIFFERENTIAL TRAVEL-----.032 MAX
OVERTRAVEL-----.090 MIN

ELECTRICAL DATA

CONTACT ARRANGEMENT
S P D T

15.1A 1/2HP 125 OR 250 VAC
1/2A 125 VDC, 1/4A 250 VDC
5A 125 VAC "L"



SCALE FULL

DO NOT SCALE PRINT

TOLERANCES

APPLY TO DESIGN UNITS. CONVERSIONS ARE ONLY FOR
REFERENCE. UNLESS NOTED, TOLERANCES ARE ±

DIM.	TOL.	DIM.	TOL.
mm	mm/in	in	mm/in
NO PLACES	X	1/64	X X
ONE PLACE	X, X	0.4/0.16	X X
TWO PLACES	X, XX	0.16/0.06	X, XX
THREE PLACES	X, XXX	0.06/0.02	X, XXX
ANGLES			

SI METRIC

US CUSTOMARY

DESIGN UNITS



WEIGHT