



注記
NOTES

1. 各部の反りは0.5最大。
WARPING : 0.5 MAX.
2. サークット NO. は NO. "1" のみ表示。
CIRCUIT NO. : 1 ONLY.

24.9	19.8	39-01-1065	5195-063	6
20.94	15.84	39-01-1055	5195-053	5
13.02	7.92	39-01-1035	5195-033	3
9.06	3.96	39-01-1025	5195-023	2
B	A	EDP NO.	MATERIAL NO.	極数 NO. OF CKTS.
			MODEL NO.	5195-N3

REVISED EC NO: J2009-0049 DRWN: MAKURAA 2008/07/23 CHKD: T. HARIYAMA 2008/07/23 APPR: NUKITA 2008/11/14 G	DESCRIPTION GENERAL TOLERANCES (UNLESS SPECIFIED) 10 UNDER ± 0.2 10 OVER 30 UNDER ± 0.25 30 OVER ± 0.3 ANGULAR ± 3 ° DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	DIMENSION STYLE MM ONLY	SCALE 4:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION		
		DRAWN BY T. ASAKAWA		DATE '95/5/9	TITLE SPOX 3.96 PITCH RECEPTACLE HOUSING		
		CHECKED BY S. A		DATE '95/5/9	MOLEX MOLEX INCORPORATED		
		APPROVED BY M. FUKUSHIMA		DATE '95/5/9	DOCUMENT NO. SD-5195-002	SHEET NO. 1 OF 1	
MATERIAL ナイロン66, UL94V-0 NYLON66, UL94V-0		SIZE A3 THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION					