TE Internal #: 1-2823446-7

Standard Circular Connectors, Cable-to-Cable, 4 Position, Sealable,

Wire & Cable, Signal, Cable Mount (Free-Hanging), Nickel, Brass

View on TE.com >



Connectors > Circular Connectors > Standard Circular Connectors > M12 Straight Crimped Strain Relief











Connector System: Cable-to-Cable

Number of Positions: 4

Sealable: Yes

Connector & Contact Terminates To: Wire & Cable

Contact Current Rating (Max): 4A

Environmental Protection Type

All M12 Straight Crimped Strain Relief (53)

Features

Product Type Features

Troduct Type reductor	
Product Type	Connector Kit
Connector System	Cable-to-Cable
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable
Circular Connector Type	Receptacle
Shell Type	Full Metal Shell
Configuration Features	
Number of Positions	4
Contacts Preloaded	No
Electrical Characteristics	
Operating Voltage	50 VDC
Body Features	

Elastomer Sealed



Weight 25 g[.0552 lb] Shell Plating Material Nickel Shell Base Material Brass Circular Connector Insulation Material Type Low Fire Hazard Thermoplastic Hermetically Sealed Yes Contact Features Contact Current Rating (Max) 4 A Circular Connector Contact Type Socket Mechanical Attachment Connector Mounting Type Cable Mount (Free-Hanging) Polarization Code D Mating Alignment Type Keyed Mating Retention With Dimensions Compatible Insulation Diameter Range 8.2 mm Wire Size 22 AWG Usage Conditions IP Water Sealing Level IP67 IP Dust Sealing Level 6 Operating Temperature Range 40 - 70 °C, -40 - 85 °C[-40 - 158 °F][-40 - 185 °F]
Shell Plating Material Nickel Shell Base Material Brass Circular Connector Insulation Material Type Low Fire Hazard Thermoplastic Hermetically Sealed Yes Contact Features Contact Current Rating (Max) 4 A Circular Connector Contact Type Socket Mechanical Attachment Connector Mounting Type Cable Mount (Free-Hanging) Polarization Code D Mating Alignment Type Keyed Mating Retention With Dimensions Compatible Insulation Diameter Range 8.2 mm Wire Size 22 AWG Usage Conditions IP Water Sealing Level IP67 IP Dust Sealing Level 6 Operating Temperature Range 40 – 70 °C, 40 – 85 °C[40 – 158 °F][40 –
Circular Connector Insulation Material Type Hermetically Sealed Yes Contact Features Contact Current Rating (Max) Circular Connector Contact Type Socket Mechanical Attachment Connector Mounting Type Cable Mount (Free-Hanging) Polarization Code D Mating Alignment Type Mating Retention With Dimensions Compatible Insulation Diameter Range Wire Size Usage Conditions IP Water Sealing Level IP Dust Sealing Level Operating Temperature Range 40 – 70 °C, -40 – 85 °C[-40 – 158 °F][-40 –
Hermetically Sealed Yes Contact Features Contact Current Rating (Max) 4 A Circular Connector Contact Type Socket Mechanical Attachment Connector Mounting Type Cable Mount (Free-Hanging) Polarization Code D Mating Alignment Type Keyed Mating Retention With Dimensions Compatible Insulation Diameter Range 8.2 mm Wire Size 22 AWG Usage Conditions IP Water Sealing Level IP67 IP Dust Sealing Level 6 Operating Temperature Range -40 -70 °C, 40 -85 °C[40 - 158 °F][40 -
Contact Current Rating (Max) Circular Connector Contact Type Socket Mechanical Attachment Connector Mounting Type Cable Mount (Free-Hanging) Polarization Code D Mating Alignment Type Keyed Mating Retention With Dimensions Compatible Insulation Diameter Range Wire Size 22 AWG Usage Conditions IP Water Sealing Level IP Dust Sealing Level Operating Temperature Range 40 – 70 °C, -40 – 85 °C[-40 – 158 °F][-40 –
Contact Current Rating (Max) Circular Connector Contact Type Socket Mechanical Attachment Connector Mounting Type Cable Mount (Free-Hanging) Polarization Code D Mating Alignment Type Keyed Mating Retention With Dimensions Compatible Insulation Diameter Range Wire Size 22 AWG Usage Conditions IP Water Sealing Level IP Dust Sealing Level Operating Temperature Range 40 – 70 °C, -40 – 85 °C[-40 – 158 °F][-40 –
Circular Connector Contact Type Mechanical Attachment Connector Mounting Type Cable Mount (Free-Hanging) Polarization Code D Mating Alignment Type Keyed Mating Retention With Dimensions Compatible Insulation Diameter Range Wire Size 22 AWG Usage Conditions IP Water Sealing Level IP Dust Sealing Level Operating Temperature Range 40 – 70 °C, -40 – 85 °C[-40 – 158 °F][-40 –
Mechanical Attachment Connector Mounting Type Cable Mount (Free-Hanging) Polarization Code D Mating Alignment Type Keyed Mating Retention With Dimensions Compatible Insulation Diameter Range 8.2 mm Wire Size 22 AWG Usage Conditions IP Water Sealing Level IP67 IP Dust Sealing Level 6 Operating Temperature Range -40 – 70 °C, -40 – 85 °C[-40 – 158 °F][-40 –
Connector Mounting Type Cable Mount (Free-Hanging) Polarization Code D Mating Alignment Type Keyed Mating Retention With Dimensions Compatible Insulation Diameter Range Wire Size 22 AWG Usage Conditions IP Water Sealing Level IP Dust Sealing Level Operating Temperature Range -40 - 70 °C, -40 - 85 °C[-40 - 158 °F][-40 -
Polarization Code Mating Alignment Type Keyed Mating Retention With Dimensions Compatible Insulation Diameter Range 8.2 mm Wire Size 22 AWG Usage Conditions IP Water Sealing Level IP Dust Sealing Level Operating Temperature Range 40 – 70 °C, -40 – 85 °C[-40 – 158 °F][-40 –
Mating Alignment Type Keyed Mating Retention With Dimensions Compatible Insulation Diameter Range 8.2 mm Wire Size 22 AWG Usage Conditions IP Water Sealing Level IP67 IP Dust Sealing Level 6 Operating Temperature Range -40 – 70 °C, -40 – 85 °C[-40 – 158 °F][-40 –
Mating Retention With Dimensions Compatible Insulation Diameter Range 8.2 mm Wire Size 22 AWG Usage Conditions IP Water Sealing Level IP67 IP Dust Sealing Level 6 Operating Temperature Range -40 – 70 °C, -40 – 85 °C[-40 – 158 °F][-40 –
Dimensions Compatible Insulation Diameter Range 8.2 mm Wire Size 22 AWG Usage Conditions IP Water Sealing Level IP67 IP Dust Sealing Level 6 Operating Temperature Range -40 – 70 °C, -40 – 85 °C[-40 – 158 °F][-40 –
Compatible Insulation Diameter Range 8.2 mm Wire Size 22 AWG Usage Conditions IP Water Sealing Level IP67 IP Dust Sealing Level 6 Operating Temperature Range -40 – 70 °C, -40 – 85 °C[-40 – 158 °F][-40 –
Wire Size 22 AWG Usage Conditions IP Water Sealing Level IP67 IP Dust Sealing Level 6 Operating Temperature Range -40 - 70 °C, -40 - 85 °C[-40 - 158 °F][-40 -
Usage Conditions IP Water Sealing Level IP Dust Sealing Level Operating Temperature Range IP 67 6 -40 – 70 °C, -40 – 85 °C[-40 – 158 °F][-40 –
IP Water Sealing LevelIP67IP Dust Sealing Level6Operating Temperature Range-40 - 70 °C, -40 - 85 °C[-40 - 158 °F][-40 -
IP Dust Sealing Level 6 Operating Temperature Range -40 - 70 °C, -40 - 85 °C[-40 - 158 °F][-40 -
Operating Temperature Range -40 – 70 °C, -40 – 85 °C[-40 – 158 °F][-40 –
Operation/Application
Durability Rating 250 Cycles
Circuit Application Signal
Shielded Yes
Industry Standards
UL Flammability Rating UL 94V-0
Packaging Features
Packaging Quantity 1
Other
Field Serviceable Yes



Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUL 2021 (219) SVHC > Threshold: Pb (3.5% in Component) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts

















Customers Also Bought















Documents

Product Drawings

M12 D-F-4 CRIMP ST CAT 7 RADOX 8.2MM,H&S

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-2823446-7_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-2823446-7_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-2823446-7_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Standard Circular Connectors, Cable-to-Cable, 4 Position, Sealable, Wire & Cable, Signal, Cable Mount (Free-Hanging), Nickel, Brass



Datasheets & Catalog Pages

M12 RAIL CONNECTOR SERIES

English

M12 Rail Straight Connector

English

Product Specifications

Product Specification

English