



Date	SYM	REVISION RECORD	AUTH	DR.	CK.
8/06/14	D	UPDATED TO ROHS 2 COMPLIANT	T.B.	B.S.	
3/10/17	E	ADDED MOUNTING INSTRUCTION	T.B.	B.S.	
5/19/17	F	ADDED DIM. 150.0, 5.0	T.B.	B.S.	



SPECIFICATIONS

Plastic material - Polypropylene
 Flammability Rating -UL94-HB, UL File NO. E216959
 Temperature Range: -10°C to +100°C
 Springs - Nickel Plated Spring Steel
 Wire - 6" Long, 26 AWG, UL1007, CSA, TR64, 300V, 80°C
 Rivets - Brass, Nickel Plated
 CONTACT RESISTANCE: UNDER 50mΩ FOR +/- CONTACTS PER EIA-540J000
 ROHS 2 COMPLIANT
 MOUNTING INSTRUCTION:
 USE 4-40 MACHINE SCREWS OR EYELETS OR EQUIVALENT.
 ALSO ADHESIVES AND DOUBLE SIDED TAPES WORK WELL.

Tolerance (Except as noted)	 Memory Protection Devices, Inc 200 Broad Hollow Road, Farmingdale, New York 11735	Scale	Drawn By B.S.
		1.5=1	Approved By T.B.
decimal ±.5 (.020)	Title SIX "C" CELL HOLDER WITH 6" WIRE LEADS		
Fractional ± .8 (.030)	Date 5/19/17	Drawing Number BH26CW	
Angular ± 3°			