

General ordering data	
Order No.	1784780000
Part designation	SAIBM 5/8S M12 5P B-COD
Version	Sensor/Actuator plug-in connector, M12, Female
	socket, straight, screw
EAN	4032248191864

Qty. 1 pc(s).

Technical data	
Ambient temperature, max.	85 °C
Ambient temperature, min.	-25 °C
Bus line connection via □	screw
Cable connection diameter	68 mm (PG9)
Cable diameter, max.	8 mm
	_

Cable diameter, min
Cable gland
PG 9
Connection cross-section
0.25

Connection cross-section 0.25...0.75 mm² (B-COD) / 0.14...0.5 mm² (D-COD)

Connection cross-section, max. 0.75 mm²
Connection cross-section, min. 0.25 mm²

Connection type PE Screw connection

Contact surface CuSnZn (B-COD) / gold-plated (D-COD)

Contact tube diameter M12

Drawing with dimensions

Housing material CuZn

Ordering data, title 4- and 5-pole, straight

Protection class IP 67 Rated current 4 A

Wiring diagram

No. of poles

Version Female socket, straight

Approvals

Approvals institutes 

\[ \begin{align\*}
\pi\_a & \\
\pi\_b & \\
\pi



Classifications	
ETIM 2.0	EC000516
ETIM 3.0	EC002062
eClass 4.1	27-26-07-01
eClass 5.0	27-26-07-01
eClass 5.1	27-26-07-01

## Similar products

Order No.		Version
1784750000	SAIB-M-5/8S M12 5P A-COD	Sensor/Actuator plug-in connector, M12, Female socket, straight, screw
1892130000	SAIBM-4/8S-M12-4P D-COD	Sensor/Actuator plug-in connector, M12, screw
1784740000	SAIS-M-5/8S M12 5P A-COD	Sensor/Actuator plug-in connector, M12, pin, straight, screw
1784790000	SAISM 5/8S M12 5P B-COD	Sensor/Actuator plug-in connector, M12, pin, straight, screw
1892120000	SAISM-4/8S-M12-4P D-COD	Sensor/Actuator plug-in connector, M12, screw

