



Application Tooling Specification Sheet



Order No. 63824-7500

FEATURES

This extraction tool is for the removal of crimped terminals from housing series 34894

SCOPE

<u>Products</u>: CTX50 sealed contacts for the Mini50™ connection system.

Housing Series No.	Terminal Series No.	Terminal Order No.			
34894	34905	34905-2443	34905-2444	34905-3443	34905-3444


DESCRIPTION:

This extractor tool is 71.00 mm (2.80 in.) long by 6.35mm (.25 in.) in wide.

OPERATION:


When removing a damaged crimped terminal from the Mini50™ sealed housing, follow the steps below:

1. Position the extraction tool blade into the small square slot (in line with the terminal to be removed) in the front face of the housing. See Figure 1.



Order No: ATS-638247500 Release Date: 03-20-17 Revision: A Revision Date: 03-20-17

- 2. Push the crimped wire forward in the direction of the arrow before using the extractor tool.
- 3. Continue to push the extractor tool into the square slot until it clicks or comes to a stop.
- 4. This should separate the latch from the terminal. Do not force the extractor tool any further; otherwise, it may damage the housing.
- 5. Holding the extractor tool against the housing, gently pull the crimped wire out of the connector. See Figure 2.



CAUTION: This extractor tool should be used to extract the terminal only. Using it for unintended purposes may cause injury or damage to parts. Be careful not to deform the end of the terminal.

CAUTION: Molex specifications are valid only when used with Molex terminals, applicators and tooling.

Application Tooling Support

Phone: +1-402-458-TOOL (8665)
E-Mail: applicationtooling@molex.com
Website: www.molex.com/applicationtooling

Order No: ATS-638247500 Release Date: 03-20-17 **UNCONTROLLED COPY** Page 2 of 2 Revision: A Revision Date: 03-20-17