



- 注記  
NOTES
- 各部の反りは0.5最大。  
WARPING : 0.5 MAX.
  - サーキットNO.はNO."1"のみ表示。  
CIRCUIT NO. : 1 ONLY.

36.78	31.68	09-50-1092	5195-092	9
28.86	23.76	09-50-1072	5195-072	7
20.94	15.84	09-50-1052	5195-052	5
B	A	EDP NO.	MATERIAL NO.	極数 NO. OF CXTS.

サーキットNO. CIRCUIT NO.    ENG. NO.    トレードマーク TRADE MARK

REVISED EC NO: J2009-0049 DRWN: MAKURAA 2008/07/23 CHKD: T. HARUYAMA 2008/07/23 APPR: NUKITA 2008/11/14	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY	SCALE 4:1	DESIGN UNITS METRIC	MODEL NO. 5195-N2
	10 UNDER	± 0.2	DRAWN BY T. YASUI	DATE '96/4/9	TITLE SPOX 3.96 PITCH RECEPTACLE HOUSING	
	10 OVER 30 UNDER	± 0.25	CHECKED BY S. A	DATE '96/4/10		
	30 OVER	± 0.3	APPROVED BY M. FUKUSHIMA	DATE '96/4/10		
	ANGULAR ± 3 °	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	MATERIAL NO.	DOCUMENT NO.	MOLEX INCORPORATED	SHEET NO. 1 OF 1
			SIZE A3	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		

材料 MATERIAL  
ナイロン66, UL94V-2  
NYLON66, UL94V-2