

170 Brown

Friction Tape



Technical Data Sheet				October 2017	
Description and Features	rubber adhes 170 Friction • Frictione • Adheres	ive compound.	distinctive rubber on sides	coated on both sid	
Materials	Backing Cotton fabric	Adhesive Rubber	Color Brown	Standard Size Width x Length 51 mm x 21m (2 in. x 69 ft.) Other sizes are available upon request	
Technical Properties	Characteristic Thickness (mm) Tensile strength (N/cm) Adhesion Standard (mm/min) Oven test (mm/min) Copper corrosion (visual) Dielectric breakdown (V)			Typical Value 0,38 70 380 380 Pass 1200	Test Method ASTM D 69 ASTM D 69 ASTM D 69 ASTM D 69 ASTM D 69 ASTM D 69
Recommended Uses	and wire. Ter	mporary binding and	I harnessing tape	sion and penetration and has a multitude es, it effects a non-sl	of miscellaneous
Storage	In original packaging, placed in horizontal position under cover and temperature between 5°C and 35 °C.				
Shelf Life	24 months from date of manufacture.				

Information provided is for reference only. Data in table represent average test results and are not to be used for specification purposes. The product user should make his/her own tests to determine the product's suitability for the intended use

LIMITED WARRANTY: Plymouth warrants that its Product will substantially conform to that products written specifications for a period of one (1) year from the date of shipment, (Unless provided otherwise). Plymouth makes no warrants to the distributor, its customers, or the product's end user of the products merchantability and/or suitability for his/its intended use or purpose, and buyer shall assume all risks associated therewith. Provided that the product is proved to be defective within the terms described above, and provided byer shall have first compiled with all return policies of Plymouth, PLYMOUTH'S SOLE OBLIGATION AND BUYER'S EXCLUSIVE REMEDY UNDER THIS PRODUCT WARRANTY SHALL BE TO REPLACE SUCH QUANTITY OF THE PRODUCT AS IS PROVED TO BE DEFECTIVE WITHIN THE TIME PERIOD SPECIFIED ABOVE, EXCEPT AS EXPRESSLY SET FORTH HEREIN, PLYMOUTH MAKES NO OTHER ARRANTIES, EXPRESS OR IMPLIED. In no event shall Plymouth be liable for collateral, consequential, indirect or incidental damages arising out of, or connected in any way with the supply of products. (Rev. 1/2017-2019)

Plymouth Rubber Europa, S.A. • Ctra. Porriño-Salceda, km 1,5 36400 PORRIÑO - SPAIN • Tel.: +34 986 330 562 • Fax: +34 986 336 926 www.plymouthrubber.com • info@plymouthrubber.com