



HRS DRAWING FOR REFERENCE

CODE No.	PART No.	CONTACT	A	B
CL541-0136-9	DF1-2S-2.5C	2	8.0±0.3	2.5±0.2
CL541-0137-1	DF1-3S-2.5C	3	10.5±0.3	5.0±0.2
CL541-0138-4	DF1-4S-2.5C	4	13.0±0.3	7.5±0.2
CL541-0139-7	DF1-5S-2.5C	5	15.5±0.3	10.0±0.2
CL541-0140-6	DF1-6S-2.5C	6	18.0±0.3	12.5±0.2
CL541-0141-9	DF1-7S-2.5C	7	20.5±0.3	15.0±0.2
CL541-0142-1	DF1-8S-2.5C	8	23.0±0.3	17.5±0.2
CL541-0143-4	DF1-9S-2.5C	9	25.5±0.3	20.0±0.2
CL541-0144-7	DF1-10S-2.5C	10	28.0±0.3	22.5±0.2
CL541-0145-0	DF1-11S-2.5C	11	30.5±0.3	25.0±0.2
CL541-0146-2	DF1-12S-2.5C	12	33.0±0.3	27.5±0.2
CL541-0147-5	DF1-13S-2.5C	13	35.5±0.4	30.0±0.4
CL541-0148-8	DF1-14S-2.5C	14	38.0±0.4	32.5±0.4
CL541-0149-0	DF1-15S-2.5C	15	40.5±0.4	35.0±0.4
CL541-0150-0	DF1-16S-2.5C	16	43.0±0.4	37.5±0.4
CL541-0152-5	DF1-18S-2.5C	18	48.0±0.4	42.5±0.4
CL541-0154-0	DF1-20S-2.5C	20	53.0±0.4	47.5±0.4

① NO RAISE AT THE CENTER OF THE HOUSING FOR 3, 4, 5, 6 AND 7 POS.
 FOR 2 POS., SINGLE RAISE IS PROVIDED AT THE CENTER.
 ② PIN NO. MARKING(1, 2, 3, 4... 20)

NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS
1	POLYAMIDE	LIGHT BROWN, UL94V-0			

UNITS	SCALE	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	5 : 1					

APPROVED : KI. AKIYAMA	10.05.11	DRAWING NO.	EDC3-162414-01
CHECKED : HK. UMEHARA	10.05.11	PART NO.	DF1-*S-2.5C
DESIGNED : HT. SATO	10.05.11	CODE NO.	CL541-
DRAWN : MI. SAKIYURA	10.05.11		