



Product Specification

G170EG01 V1

AU OPTRONICS CORPORATION

Preliminary Specification

Final Specification

| | |
|-------------------|--------------------------|
| Module | 17.0" SXGA Color TFT-LCD |
| Model Name | G170EG01 V1 |



| Customer | Date |
|---|-------|
| _____ | _____ |
| Approved by | |
| Note: This Specification is subject to change without notice. | |

| Checked & Approved by | Date |
|--|------------|
| <i>Vito Huang</i> | 2013/06/24 |
| Prepared by | |
| <i>Elsie Kuo</i> | 2013/06/24 |
| Desktop Display Business Group / AU Optronics corporation | |

Contents

| | |
|--|-----------|
| 1. Handling Precautions | 5 |
| 2. General Description | 6 |
| 2.1 Display Characteristics | 6 |
| 2.2 Optical Characteristics | 7 |
| 3. Functional Block Diagram | 11 |
| 4. Absolute Maximum Ratings | 12 |
| 4.1 TFT LCD Module | 12 |
| 4.2 Backlight Unit | 12 |
| 4.3 Absolute Ratings of Environment | 12 |
| 5. Electrical characteristics | 13 |
| 5.1 TFT LCD Module | 13 |
| 5.2 Backlight Unit | 15 |
| 6. Signal Characteristic | 16 |
| 6.1 Pixel Format Image | 16 |
| 6.2 The Input Data Format | 16 |
| 6.3 Signal Description | 17 |
| 6.4 Timing Characteristics | 19 |
| 6.5 Power ON/OFF Sequence | 21 |
| 7. Connector & Pin Assignment | 22 |
| 7.1 TFT LCD Module | 22 |
| 7.2 Backlight Unit | 23 |
| 8. Reliability Test | 24 |
| 9. Label and Packaging | 25 |
| 9.1 Shipping Label (on the rear side of TFT-LCD display) | 25 |
| 9.2 Carton Package | 25 |
| 10. Mechanical Characteristics | 27 |

Record of Revision

| Version and Date | Page | Old description | New Description | Remark | | | | | | | | | | | | | | | | | | | | | | | | |
|---------------------------------|---------------------------|--|--|--------------------|---------------------------------|---------------------------|--|--------------------|--------------------|---|---------------------------|----------------------|---------|----------|--|----------------------|--------|-------|-------|---------------------|------------|---------------------|----------------|---------------------|-------|-------|----------|--|
| 0.1 2011/01/12 | All | First Edition for Customer | All | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.2 2011/01/14 | 5 | 350 (center, Typ)@7.5 mA | 350 | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 24 | <table border="1"> <thead> <tr> <th>Items</th> <th>Required Condition</th> </tr> </thead> <tbody> <tr> <td>Temperature Humidity Bias (THB)</td> <td>Ta= 50°C, 90%RH, 300hours</td> </tr> </tbody> </table> | Items | Required Condition | Temperature Humidity Bias (THB) | Ta= 50°C, 90%RH, 300hours | <table border="1"> <thead> <tr> <th>Items</th> <th>Required Condition</th> </tr> </thead> <tbody> <tr> <td>Temperature Humidity Bias (THB)</td> <td>Ta= 50°C, 80%RH, 300hours</td> </tr> </tbody> </table> | Items | Required Condition | Temperature Humidity Bias (THB) | Ta= 50°C, 80%RH, 300hours | | | | | | | | | | | | | | | | | |
| Items | Required Condition | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Temperature Humidity Bias (THB) | Ta= 50°C, 90%RH, 300hours | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Items | Required Condition | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Temperature Humidity Bias (THB) | Ta= 50°C, 80%RH, 300hours | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.3 2011/01/24 | 11 |  |  | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 26 | Thickness= 15.8 mm | Thickness= 18.0 mm | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.4 2011/04/06 | 5, 6 | Optical ResponseTime= 5 ms | Optical ResponseTime= 30 ms | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 5 | This module does not contain an inverter card for backlight. | This module embeds an LED driver on it. | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 5 | Weight: 1800 (g) Typ. | Weight: 1350 (g) Typ. | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 11 | 4.2 Backlight Unit <table border="1"> <thead> <tr> <th>Item</th> <th>Symbol</th> <th>Min.</th> <th>Max.</th> <th>Unit</th> <th>Conditions</th> </tr> </thead> <tbody> <tr> <td>LED Current</td> <td>ICFL</td> <td>-</td> <td>110</td> <td>[mA]rms</td> <td>Note 1,2</td> </tr> </tbody> </table> | Item | Symbol | Min. | Max. | Unit | Conditions | LED Current | ICFL | - | 110 | [mA]rms | Note 1,2 | 4.2 Backlight Unit <table border="1"> <thead> <tr> <th>Item</th> <th>Symbol</th> <th>Min.</th> <th>Max.</th> <th>Unit</th> <th>Conditions</th> </tr> </thead> <tbody> <tr> <td>LED Forward Current</td> <td>I_f</td> <td>-</td> <td>120</td> <td>[mA]</td> <td>Note 1,2</td> </tr> </tbody> </table> | Item | Symbol | Min. | Max. | Unit | Conditions | LED Forward Current | I _f | - | 120 | [mA] | Note 1,2 | |
| Item | Symbol | Min. | Max. | Unit | Conditions | | | | | | | | | | | | | | | | | | | | | | | |
| LED Current | ICFL | - | 110 | [mA]rms | Note 1,2 | | | | | | | | | | | | | | | | | | | | | | | |
| Item | Symbol | Min. | Max. | Unit | Conditions | | | | | | | | | | | | | | | | | | | | | | | |
| LED Forward Current | I _f | - | 120 | [mA] | Note 1,2 | | | | | | | | | | | | | | | | | | | | | | | |
| | 23 | No pins drawing of LED driver board | New add pins drawing | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.0 2011/09/30 | 6 | Without RGB color coordinate | <table border="1"> <tbody> <tr> <td>Red x^o</td> <td>0.598</td> <td>0.648</td> <td>0.698</td> </tr> <tr> <td>Red y^o</td> <td>0.289</td> <td>0.339</td> <td>0.389</td> </tr> <tr> <td>Green x^o</td> <td>0.273</td> <td>0.323</td> <td>0.373</td> </tr> <tr> <td>Green y^o</td> <td>0.563</td> <td>0.613</td> <td>0.663</td> </tr> <tr> <td>Blue x^o</td> <td>0.093</td> <td>0.143</td> <td>0.193</td> </tr> <tr> <td>Blue y^o</td> <td>0.020</td> <td>0.070</td> <td>0.120</td> </tr> </tbody> </table> | Red x ^o | 0.598 | 0.648 | 0.698 | Red y ^o | 0.289 | 0.339 | 0.389 | Green x ^o | 0.273 | 0.323 | 0.373 | Green y ^o | 0.563 | 0.613 | 0.663 | Blue x ^o | 0.093 | 0.143 | 0.193 | Blue y ^o | 0.020 | 0.070 | 0.120 | |
| Red x ^o | 0.598 | 0.648 | 0.698 | | | | | | | | | | | | | | | | | | | | | | | | | |
| Red y ^o | 0.289 | 0.339 | 0.389 | | | | | | | | | | | | | | | | | | | | | | | | | |
| Green x ^o | 0.273 | 0.323 | 0.373 | | | | | | | | | | | | | | | | | | | | | | | | | |
| Green y ^o | 0.563 | 0.613 | 0.663 | | | | | | | | | | | | | | | | | | | | | | | | | |
| Blue x ^o | 0.093 | 0.143 | 0.193 | | | | | | | | | | | | | | | | | | | | | | | | | |
| Blue y ^o | 0.020 | 0.070 | 0.120 | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 6 | <table border="1"> <tbody> <tr> <td>Contrast Ratio</td> <td>-</td> <td>-</td> <td>800</td> <td>800</td> <td>-</td> <td>4</td> </tr> </tbody> </table> | Contrast Ratio | - | - | 800 | 800 | - | 4 | <table border="1"> <tbody> <tr> <td>Contrast Ratio</td> <td>-</td> <td>-</td> <td>800</td> <td>800</td> <td>-</td> <td>4</td> </tr> </tbody> </table> | Contrast Ratio | - | - | 800 | 800 | - | 4 | | | | | | | | | | | |
| Contrast Ratio | - | - | 800 | 800 | - | 4 | | | | | | | | | | | | | | | | | | | | | | |
| Contrast Ratio | - | - | 800 | 800 | - | 4 | | | | | | | | | | | | | | | | | | | | | | |
| | 24 | Without EMI item is RA list | <table border="1"> <tbody> <tr> <td>EMI</td> <td>CEM32</td> <td>CEM32</td> <td>CEM32</td> <td>CEM32</td> <td>CEM32</td> <td>CEM32</td> </tr> </tbody> </table> | EMI | CEM32 | CEM32 | CEM32 | CEM32 | CEM32 | CEM32 | | | | | | | | | | | | | | | | | | |
| EMI | CEM32 | CEM32 | CEM32 | CEM32 | CEM32 | CEM32 | | | | | | | | | | | | | | | | | | | | | | |
| | 25 | Outside dimension of carton:434(L)mm*278(W)mm*390(H)mm | Outside dimension of carton:426(L)mm*270(W)mm*375(H)mm | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.1 2012/02/01 | 5 | Operation temperature -30 to +85 | Operation temperature -30 to +70 | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.2 2012/05/25 | 6 | No Color Gamut spec | Add Color Gamut 72% | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.3 2012/07/12 | | Change View Angle Spec & Delete | Change View Angle spec(CR=10) & Delete | | | | | | | | | | | | | | | | | | | | | | | | | |



Product Specification

G170EG01 V1

AU OPTRONICS CORPORATION

| | | | | |
|---------------|----|--|--|--|
| | | View Angle spec(CR=5) | View Angle spec(CR=5) Typ. From L85/R85/U80/D80 to L80/R80/U60/D80 Min From L70/R70/U70/D70 to L70/R70/U50/D70 | |
| 1.4 2013/6/24 | 6 | Operation temperature -30 to +70 | Operation temperature -30 to +85 | |
| | 25 | 9.2 Carton Package Max capacity : 8 TFT-LCD module per carton Max weight: 14 kg per carton Outside dimension of carton, 426(L)mm*270(W)mm*375(H)mm | 9.2 Carton Package Max capacity : 8 TFT-LCD module per carton Max weight: 18 kg per carton Outside dimension of carton, 434(L)mm*278(W)mm*391(H)mm | |
| | 26 | No palletizing info | Add palletizing info | |

1. Handling Precautions

- 1) Since front polarizer is easily damaged, pay attention not to scratch it.
- 2) Be sure to turn off power supply when inserting or disconnecting from input connector.
- 3) Wipe off water drop immediately. Long contact with water may cause discoloration or spots.
- 4) When the panel surface is soiled, wipe it with absorbent cotton or other soft cloth.
- 5) Since the panel is made of glass, it may break or crack if dropped or bumped on hard surface.
- 6) Since CMOS LSI is used in this module, take care of static electricity and insure human earth when handling.
- 7) Do not open or modify the Module Assembly.
- 8) Do not press the reflector sheet at the back of the module to any directions.
- 9) In case if a Module has to be put back into the packing container slot after once it was taken out from the container, do not press the center of the LED light bar edge. Instead, press at the far ends of the LED light bar edge softly. Otherwise the TFT Module may be damaged.
- 10) At the insertion or removal of the Signal Interface Connector, be sure not to rotate nor tilt the Interface Connector of the TFT Module.
- 11) After installation of the TFT Module into an enclosure, do not twist nor bend the TFT Module even momentary. At designing the enclosure, it should be taken into consideration that no bending/twisting forces are applied to the TFT Module from outside. Otherwise the TFT Module may be damaged.
- 12) Small amount of materials having no flammability grade is used in the LCD module. The LCD module should be supplied by power complied with requirements of Limited Power Source (IEC60950 or UL1950), or be applied exemption.

2. General Description

This specification applies to the 17 inch Color TFT-LCD Module G170EG01 V1.

The display supports the SXGA+ (1280(H) x 1024(V)) screen format and 16.7M colors (RGB 6-bits+Hi-FRC data). All input signals are 2 Channel LVDS interface compatible.

This module embeds an LED driver on it.

2.1 Display Characteristics

The following items are characteristics summary on the table under 25 °C condition:

| Items | Unit | Specifications |
|---|----------------------|---|
| Screen Diagonal | [mm] | 432 (17.0") |
| Active Area | [mm] | 337.920(H) × 270.336(V) |
| Pixels H x V | | 1280 × 3(RGB) × 1024 |
| Pixel Pitch | [mm] | 0.264(per one triad) × 0.264 |
| Pixel Arrangement | | R.G.B. Vertical Stripe |
| Display Mode | | Normally White |
| White Luminance | [cd/m ²] | 350 |
| Contrast Ratio | | 800 : 1 (Typ) |
| Optical ResponseTime | [msec] | 30 (Typ) |
| Nominal Input Voltage VDD | [Volt] | +5.0 (Typ) |
| Power Consumption (VDD line + LED line) | [Watt] | 22 W (Typ.) (with LED driver, all black pattern) |
| Weight | [Grams] | 1350 Typ. |
| Physical Size (H x V x D) | [mm] | 358.5(H) x 296.5(V) Typ. x 18.0(D) Max |
| Electrical Interface | | Dual Channel LVDS |
| Surface Treatment | | Anti-glare type, Hardness 3H |
| Support Color | | 16.7M colors (RGB 6-bits +Hi-FRC data) |
| Temperature Range Operating Storage (Non-Operating) | [°C] [°C] | -30 to +85 -30 to +85 |
| RoHS Compliance | | RoHS Compliance |

2.2 Optical Characteristics


The optical characteristics are measured under stable conditions at 25°C (Room Temperature):

| Item | Unit | Conditions | Min. | Typ. | Max. | Note |
|---|----------------------|--------------------------------------|----------|----------|-------|------|
| Viewing Angle | [degree] | Horizontal (Right) CR = 10 (Left) | 70 70 | 80 80 | - | 1 |
| | | Vertical (Up) CR = 10 (Down) | 50 70 | 60 80 | - | |
| Luminance Uniformity | [%] | 9 Points | 75 | 80 | - | 2, 3 |
| Optical Response Time | [msec] | Rising | - | 20 | 25 | 4, 6 |
| | | Falling | - | 10 | 15 | |
| | | Rising + Falling | - | 30 | 40 | |
| Color / Chromaticity Coordinates (CIE 1931) | | Red x | 0.598 | 0.648 | 0.698 | 4 |
| | | Red y | 0.289 | 0.339 | 0.389 | |
| | | Green x | 0.273 | 0.323 | 0.373 | |
| | | Green y | 0.563 | 0.613 | 0.663 | |
| | | Blue x | 0.093 | 0.143 | 0.193 | |
| | | Blue y | 0.020 | 0.070 | 0.120 | |
| | | White x | 0.263 | 0.313 | 0.363 | |
| White y | 0.279 | 0.329 | 0.379 | | | |
| White Luminance (At LED= 110mA) | [cd/m ²] | | 280 | 350 | - | 4 |
| Contrast Ratio | | | 600 | 800 | - | 4 |
| Cross Talk (At 75Hz) | [%] | | - | - | 1.5 | 5 |
| Flicker | [dB] | | - | - | -20 | 7 |
| Color Gamut | [%] | | | 72 | | |


Optical Equipment: BM-5A, BM-7, PR880, or equivalent

Note 1: Definition of viewing angle

Viewing angle is the measurement of contrast ratio ≥ 10 , at the screen center, over a 180° horizontal and 180° vertical range (off-normal viewing angles). The 180° viewing angle range is broken down as follows; 90° (θ) horizontal left and right and 90° (Φ) vertical, high (up) and low (down). The measurement direction is typically perpendicular to the display surface with the screen rotated about its center to develop the desired measurement viewing angle.



Note 2: 9 points position




Note 3: The luminance uniformity of 9 points is defined by dividing the maximum luminance values by the minimum test point luminance

$$\delta_{w9} = \frac{\text{Maximum Luminance of 9 points}}{\text{Minimum Luminance of 9 points}}$$

Note 4: Measurement method

The LCD module should be stabilized at given temperature for 30 minutes to avoid abrupt temperature change during measuring. In order to stabilize the luminance, the measurement should be executed after lighting Backlight for 30 minutes in a stable, windless and dark room.




Note 5: Definition of Cross Talk (CT)

$$CT = | YB - YA | / YA \times 100 (\%)$$

Where


YA = Luminance of measured location without gray level 0 pattern (cd/m²)

YB = Luminance of measured location with gray level 0 pattern (cd/m²)




Note 6: Definition of response time:


The output signals of photo detector are measured when the input signals are changed from “Full Black” to “Full White” (rising time), and from “Full White” to “Full Black” (falling time), respectively. The response time is interval between the 10% and 90% of amplitudes. Please refer to the figure as below.



Note 7: Subchecker Pattern




Method: Record dBV & DC value with (WESTAR)TRD-100



$$\text{Flicker (dB)} = 20 \log \frac{\text{AC Level(at 30 Hz)}}{\text{DC Level}}$$

3. Functional Block Diagram

The following diagram shows the functional block of the 17.0 inches Color TFT-LCD Module:



PCBA Connector:

JAE FI-XB30SSL-HF15
Or Compatible

LED Driver Connector:

3806K-F06Y-03R
Or Compatible

4. Absolute Maximum Ratings

Absolute maximum ratings of the module is as following:

4.1 TFT LCD Module

| Item | Symbol | Min | Max | Unit | Conditions |
|-------------------------|--------|------|-----|--------|-----------------|
| Logic/LCD Drive Voltage | VIN | -0.3 | 6 | [Volt] | Note 1,2 |

4.2 Backlight Unit

| Item | Symbol | Min | Max | Unit | Conditions |
|---------------------|----------------|-----|-----|------|-----------------|
| LED Forward Current | I _F | - | 120 | [mA] | Note 1,2 |


4.3 Absolute Ratings of Environment

| Item | Symbol | Min | Max | Unit | Conditions |
|-----------------------|--------|-----|-----|-------|---------------|
| Operating Temperature | TOP | -30 | +85 | [°C] | Note 3 |
| Operation Humidity | HOP | 8 | 90 | [%RH] | |
| Storage Temperature | TST | -30 | +85 | [°C] | |
| Storage Humidity | HST | 8 | 90 | [%RH] | |

Note 1: With in Ta (25□)

Note 2: Permanent damage to the device may occur if exceed maximum values

Note 3: For quality performance, please refer to AUO IIS (Incoming Inspection Standard).



5. Electrical characteristics



5.1 TFT LCD Module

5.1.1 Power Specification

Input power specifications are as follows:

| Symbol | Parameter | Min. | Typ. | Max. | Unit | Condition |
|--------|--|------|------|------|----------|--|
| VCC | Logic/LCD Drive Voltage | 4.5 | 5.0 | 5.5 | [Volt] | ±10% |
| ICC | Input Current | - | 1.05 | 1.16 | [A] | V _{in} =5V , All Black Pattern, at 75Hz |
| IRush | Inrush Current | - | - | 3.0 | [A] | Note |
| PCC | VCC Power | - | 5.25 | 5.8 | [Watt] | V _{in} =5V , All Black Pattern, at 75Hz |
| VCCrp | Allowable Logic/LCD Drive Ripple Voltage | - | - | 200 | [mV] p-p | With panel loading |

Note: Measurement conditions:



5.1.2 Signal Electrical Characteristics


Input signals shall be low or Hi-Z state when V_{in} is off

It is recommended to refer the specifications of SN75LVDS82DGG (Texas Instruments) in detail.

Each signal characteristics are as follows;

| Symbol | Parameter | Min | Typ | Max | Units | Condition |
|--------|--|------|------|------|-------|---------------------------------|
| VTH | Differential Input High Threshold | - | - | +100 | [mV] | VICM = 1.2V Note |
| VTL | Differential Input Low Threshold | -100 | - | - | [mV] | VICM = 1.2V Note |
| VID | Input Differential Voltage | 100 | 400 | 600 | [mV] | Note |
| VICM | Differential Input Common Mode Voltage | +1.0 | +1.2 | +1.5 | [V] | VTH/VTL = ±100mV Note |

Note: LVDS Signal Waveform



5.2 Backlight Unit

Parameter guideline LED

Following characteristics are measured under stable condition at 25°C (Room Temperature)

| Symbol | Parameter | Min. | Typ. | Max. | Unit | Remark |
|------------------|-----------------------|-------|-------|------|------|-------------------------------|
| V_{LED} | Input Voltage | 10.8 | 12 | 12.6 | Volt | |
| I_{LED} | Input Current | - | 1.18 | - | A | 100% Dimming |
| P_{LED} | Power Consumption | - | 14.16 | - | Watt | 100% Dimming |
| $I_{INRUSH LED}$ | Inrush Current | - | - | 5.1 | A | V_{LED} rising time ~ 470us |
| F_{PWM} | PWM Dimming Frequency | 200 | - | 20K | Hz | Note 1,2 |
| $V_{PWM DIM}$ | Swing Voltage High | 4.5 | 5.0 | 5.5 | Volt | |
| | Swing Voltage Low | - | - | 0.8 | Volt | |
| D_{PWM} | Dimming Duty Cycle | 10 | - | 100 | % | |
| I_F | LED Forward Current | - | 110 | - | mA | Ta = 25°C |
| $V_{LED ON/OFF}$ | On Control Voltage | 3.0 | 3.3 | 5.5 | Volt | Note 3, 4 |
| | Off Control Voltage | - | - | 0.8 | Volt | |
| Operating Life | | 50000 | - | - | Hrs | Note 5, 6 |

Note 1: PWM dimming function can be operated by PWM signal. PWM duty cycle can adjust white Luminance.
(PWM High: ON and PWM Low: OFF)

Note 2: PWM signal can not be floating and pull-down to ground when waiting.

Note 3: Enable ($V_{LED On/Off}$) must be turned on late than V_{LED} and PWM Signal.

Note 4: Enable ($V_{LED On/Off}$) must be turned off early than V_{LED} and PWM Signal.


Note 5: If G170EG01 V1 module is driven by high current or at high ambient temperature & humidity condition. The operating life will be reduced.

Note 6: Operating life means brightness goes down to 50% initial brightness. Minimum operating life time is estimated data.


6. Signal Characteristic

6.1 Pixel Format Image

Following figure shows the relationship of the input signals and LCD pixel format.



6.2 The Input Data Format



Note1: Normally, DE, VS, HS on EVEN channel are not used.

Note2: Please follow PSWG.


Note3: 8-bit in

6.3 Signal Description

The module using a pair of LVDS receiver SN75LVDS82(Texas Instruments) or compatible. LVDS is a differential signal technology for LCD interface and high speed data transfer device. Transmitter shall be SN75LVDS83(negative edge sampling) or compatible. The first LVDS port(RxOxxx) transmits odd pixels while the second LVDS port(RxExxx) transmits even pixels.

| PIN # | SIGNAL NAME | DESCRIPTION |
|-------|-------------|--|
| 1 | RxO0- | Negative LVDS differential data input (Odd data) |
| 2 | RxO0+ | Positive LVDS differential data input (Odd data) |
| 3 | RxO1- | Negative LVDS differential data input (Odd data) |
| 4 | RxO1+ | Positive LVDS differential data input (Odd data) |
| 5 | RxO2- | Negative LVDS differential data input (Odd data, H-Sync,V-Sync,DSPTMG) |
| 6 | RxO2+ | Positive LVDS differential data input (Odd data, H-Sync,V-Sync,DSPTMG) |
| 7 | GND | Power Ground |
| 8 | RxOC- | Negative LVDS differential clock input (Odd clock) |
| 9 | RxOC+ | Positive LVDS differential clock input (Odd clock) |
| 10 | RxO3- | Negative LVDS differential data input (Odd data) |
| 11 | RxO3+ | Positive LVDS differential data input (Odd data) |
| 12 | RxE0- | Negative LVDS differential data input (Even data) |
| 13 | RxE0+ | Positive LVDS differential data input (Even data) |
| 14 | GND | Power Ground |
| 15 | RxE1- | Negative LVDS differential data input (Even data) |
| 16 | RxE1+ | Positive LVDS differential data input (Even data) |
| 17 | GND | Power Ground |
| 18 | RxE2- | Negative LVDS differential data input (Even data) |
| 19 | RxE2+ | Positive LVDS differential data input (Even data) |
| 20 | RxEC- | Negative LVDS differential clock input (Even clock) |
| 21 | RxEC+ | Positive LVDS differential clock input (Even clock) |
| 22 | RxE3- | Negative LVDS differential data input (Even data) |
| 23 | RxE3+ | Positive LVDS differential data input (Even data) |
| 24 | GND | Power Ground |
| 25 | GND | Power Ground (For AUO test Aging+HVS mode) |
| 26 | NC | No contact |
| 27 | GND | Power Ground |
| 28 | VCC | +5.0V Power Supply |
| 29 | VCC | +5.0V Power Supply |
| 30 | VCC | +5.0V Power Supply |

Note1: Start from left side



Note2: Input signals of odd and even clock shall be the same timing.

Note3: Please follow PSWG.

6.4 Timing Characteristics


6.4.1 Timing Characteristics

Basically, interface timings described here is not actual input timing of LCD module but output timing of SN75LVDS82DGG (Texas Instruments) or equivalent.

| Signal | Item | Symbol | Min | Typ | Max | Unit |
|--------------------|------------|-------------------------------|-------|-------|------|------|
| Vertical Section | Period | T_v | 1034 | 1066 | 2048 | Th |
| | Active | $T_{disp(v)}$ | 1024 | 1024 | 1024 | Th |
| | Blanking | $T_{bp(v)}+T_{fp(v)}+PW_{vs}$ | 10 | 42 | 1024 | Th |
| Horizontal Section | Period | T_h | 750 | 844 | 2048 | Tclk |
| | Active | $T_{disp(h)}$ | 640 | 640 | 640 | Tclk |
| | Blanking | $T_{bp(h)}+T_{fp(h)}+PW_{hs}$ | 110 | 204 | 1408 | Tclk |
| Clock | Period | Tclk | 14.81 | 18.52 | 25 | ns |
| | Frequency | Freq | 40 | 54 | 70 | MHz |
| Frame rate | Frame rate | F | 49 | 60 | 76 | Hz |


Note : DE mode only

6.4.2 Timing Diagram



6.5 Power ON/OFF Sequence

VDD power and lamp on/off sequence is as follows. Interface signals are also shown in the chart. Signals from any system shall be Hi-Z state or low level when VDD is off.



| Parameter | Value | | | Unit |
|-----------|-------|------|------|------|
| | Min. | Typ. | Max. | |
| T1 | 0.5 | - | 10 | [ms] |
| T2 | 30 | 40 | 50 | [ms] |
| T3 | 200 | - | - | [ms] |
| T4 | 0.5 | - | 10 | [ms] |
| T5 | 10 | - | - | [ms] |
| T6 | 10 | - | - | [ms] |
| T7 | 0 | - | - | [ms] |
| T8 | 10 | - | - | [ms] |
| T9 | - | - | 10 | [ms] |
| T10 | 110 | - | - | [ms] |
| T11 | 0 | 16 | 50 | [ms] |
| T12 | - | - | 10 | [ms] |
| T13 | 1000 | - | - | [ms] |

7. Connector & Pin Assignment

Physical interface is described as for the connector on module. These connectors are capable of accommodating the following signals and will be following components.

7.1 TFT LCD Module

7.1.1 Connector

| Connector Name / Designation | Interface Connector |
|------------------------------|-------------------------------|
| Manufacturer | JAE or Compatible |
| Type Part Number | FI-XB30SSL-HF15 or Compatible |
| Mating Housing Part Number | JAE FI-X30HL or Compatible |

7.1.2 Pin Assignment

| Pin# | Signal Name | Pin# | Signal Name |
|------|------------------|------|-------------|
| 1 | RxOIN0- | 2 | RxOIN0+ |
| 3 | RxOIN1- | 4 | RxOIN1+ |
| 5 | RxOIN2- | 6 | RxOIN2+ |
| 7 | GND | 8 | RxOCLKIN- |
| 9 | RxOCLKIN+ | 10 | RxOIN3- |
| 11 | RxOIN3+ | 12 | RxEIN0- |
| 13 | RxEIN0+ | 14 | GND |
| 15 | RxEIN1- | 16 | RxEIN1+ |
| 17 | GND | 18 | RxEIN2- |
| 19 | RxEIN2+ | 20 | RxECLKIN- |
| 21 | RxECLKIN+ | 22 | RxEIN3- |
| 23 | RxEIN3+ | 24 | GND |
| 25 | GND (AGMODE+HVS) | 26 | NC |
| 27 | GND | 28 | VCC |
| 29 | VCC | 30 | VCC |



7.2 Backlight Unit

Physical interface is described as for the connector on module. These connectors are capable of accommodating the following signals and will be following components.

| | |
|-------------------------------------|------------------------------|
| Connector Name / Designation | Lamp Connector |
| Manufacturer | E&T or compatible |
| Connector Model Number | 3806K-F06Y-03R or compatible |
| Mating Connector Model Number | H208K-P06N-02B or compatible |

7.2.1 Signal for LED driver connector

| Pin# | Symbol | Signal Name |
|------|------------|----------------|
| 1 | VCC | 12V |
| 2 | VCC | 12V |
| 3 | GND | GND |
| 4 | GND | GND |
| 5 | Display on | 5V-On / 0V-Off |
| 6 | Dimming | PWM Dimming |



8. Reliability Test

Environment test conditions are listed as following table.

| Items | Required Condition | Note |
|-----------------------------------|---|------|
| Temperature Humidity Bias (THB) | Ta= 50□, 80%RH, 300hours | |
| High Temperature Operation (HTO) | Ta= 85□, 300hours | |
| Low Temperature Operation (LTO) | Ta= -30□, 300hours | |
| High Temperature Storage (HTS) | Ta= 85□, 300hours | |
| Low Temperature Storage (LTS) | Ta= -30□, 300hours | |
| Vibration Test (Non-operation) | Acceleration: 1.5 G Wave: Random Frequency: 10 - 200 - 10 Hz Sweep: 30 Minutes each Axis (X, Y, Z) | |
| Shock Test (Non-operation) | Acceleration: 50 G Wave: Half-sine Active Time: 20 ms Direction: ±X, ±Y, ±Z (one time for each Axis) | |
| Drop Test | Height: 60 cm, package test | |
| Thermal Shock Test (TST) | -20□/30min, 60□/30min, 100 cycles | |
| On/Off Test | On/10sec, Off/10sec, 30,000 cycles | |
| ESD | Contact Discharge: ± 8KV, 150pF(330Ω) 1sec, 8 points, 25 times/ point. | 1 |
| | Air Discharge: ± 15KV, 150pF(330Ω) 1sec 8 points, 25 times/ point. | |
| EMI | 30-230 MHz, limit 40 dBu V/m, 230-1000 MHz, limit 47 dBu V/m | |
| Altitude Test | Operation:10,000 ft Non-Operation:30,000 ft | |

Note1: According to EN61000-4-2, ESD class B: Some performance degradation allowed. No data lost
Self-recoverable. No hardware failures.

Note2:

- Water condensation is not allowed for each test items.
- Each test is done by new TFT-LCD module. Don't use the same TFT-LCD module repeatedly for reliability test.
- The reliability test is performed only to examine the TFT-LCD module capability.
- To inspect TFT-LCD module after reliability test, please store it at room temperature and room humidity for 24 hours at least in advance.
- No function failure occurs.

9. Label and Packaging


9.1 Shipping Label (on the rear side of TFT-LCD display)

The shipping label format is shown as below.



9.2 Carton Package

- Max capacity : 8 TFT-LCD module per carton
- Max weight: 18 kg per carton
- Outside dimension of carton:434(L)mm*278(W)mm*391(H)mm



9.3 Palletizing

| | MAX_SHIPPING BY AIR | MAX_SHIPPING BY SEA | MAX_SHIPPING BY SEA_HQ |
|-------------------------|-----------------------|-----------------------|------------------------|
| MODULE/CARTON | 8 | 8 | 7 |
| CARTON/LAYER | 8 | 8 | 8 |
| LAYER/PALLET | 3 | 3+1 | 3+2 |
| MODULE/PALLET | 192 | 256 | 280 |
| CARTON_SIZE(MM) | 434(L)*278(W)*391(H) | 434(L)*278(W)*391(H) | 434(L)*278(W)*391(H) |
| PALLET_SIZE(MM) | 1140(L)*890(W)*135(H) | 1140(L)*890(W)*135(H) | 1140(L)*890(W)*135(H) |
| TOTAL PALLET HEIGHT(MM) | 1308 | 1834 | 2258 |
| TOTAL PALLET WEIGHT(KG) | 445 | 602 | 746 |

ONE PALLET SHIPMENT EXAMPLE SHIPPING BY AIR USED

TWO PALLET SHIPMENT EXAMPLE SHIPPING BY SEA USED

TWO PALLET SHIPMENT EXAMPLE SHIPPING BY SEA_HQ USED

10. Mechanical Characteristics

