

PD10 Make & Break Load Switching

Product Facts

- Excellent for control applications
- PCB and panel mountings
- Rugged design for the most demanding applications, including seismic shock
- Small size and weight
- Low power consumption
- No heat sinks required
- Vacuum-sealed; can operate in explosive and harsh environments
- 2000 V isolation across open contacts
- Vacuum dielectric for power switching



Panel mount version shown above is applicable to both PD5 and PD10. For PD10, the two power terminals are .064" (1.63) diameter. Refer to PD5 for PCB mount dimensions.

Product Specifications


Contact Arrangement — PD10A — SPST-NO PD10B — SPST-NC PD10P*** — SPST-Latching

(Make/Break) - 20 A

Contact Form — PD10A — A** PD10B — B** PD10P*** — P** Rated Resistive Load @ 320 Vdc — 10 A Continuous Current Carry, Max. @ 85°C — PD10A and PD10B — 25 A PD10P*** — 30 A Overload @ 320 Vdc,

For factory-direct application assistance, dial 800-253-4560, ext. 2055, or 805-220-2055.

Contact Ratings*



*Based on extrapolated data. Since each application is unique, user is encouraged to verify rating in actual application. The load terminals should always be connected as follows: Common Contact (A2) positive; Other Contact negative.

Coil Data


Nominal Volts DC	12 Vdc	24 Vdc	125 Vdc
Max. Coil Voltage	14 Vdc	28 Vdc	130 Vdc
Pickup, Max. @ 85°C	8 Vdc	16 Vdc	80 Vdc
Hold, Min. @ 85°C	3.3 Vdc	10 Vdc	33 Vdc
Dropout, Min. @ -40°C	.5 Vdc	1 Vdc	5 Vdc
Coil Resistance (±10%)	70 Ω	290 Ω	4700 Ω


Ratings listed are for 25°C, sea level conditions

7-56

Catalog 5-1773450-5 Revised 3-13

Dimensions are shown for reference purposes only. Specifications subject to change. Dimensions are in millimeters unless otherwise specified.





Life, (Mechanical/Rated Load) — PD10A and PD10B — 500k cycles/10k cycles PD10P*** — 7,000 cycles

Contact Resistance, Max., End of Life — PD10A and PD10B — 0.030 ohm PD10P*** — 0.030 ohm

Dielectric at Sea Level — Power Terminals to Coil and All Other Points — PD10A and PD10B — 1,800 Vrms PD10P*** — 2,000 Vrms

Shock, 11ms, 1/2 Sine (Peak) — 25 g

Vibration, Sinusoidal (55-2000 Hz, Peak) — 5 g Operating Ambient Temperature

Range — PD10A and PD10B — -40°C to +85°C PD10P*** — -35°C to +65°C **Operate Time, Max., Including**

Bounce @ 25°C — PD10A and PD10B — 10 ms PD10P*** — 6 ms

Ordering Information

Sample Part Number

Series: ——— Contact Form:

A = SPST-NO

B = SPST-NC

P = SPST-Latching

Coil Voltage: -

- 2 = 12 Vdc, PCB Version 3 = 24 Vdc, PCB Version
- 5 = 125 Vdc, PCB Version
- A = 12 Vdc, Panel Mount Version
- B = 24 Vdc, Panel Mount Version
- C = 125 Vdc, Panel Mount Version

Power Terminals:

- 3 = PCB Solder Connection
- 5 = Stud Terminal, Panel Mount

Mounting: — 5 = PCB Mount

7 = Panel Mount

USA: +1 800 522 6752 Asia Pacific: +86 0 400 820 6015 UK: +44 800 267 666

For additional support numbers please visit www.te.com

Release Time, Max., Including

Insulation Resistance @ 500 Vdc,

Initial/End of Life — 100 mohm/50 mohm

**Contact TE for availability of other

***Not available in package shown,

package is the same as the K41P.

PD10 A A 5

7

PD10A and PD10B - 10 ms

Bounce @ 25°C

PD10P*** - 6 ms

Weight, Nominal -

71 g (.156 lb)

contact forms

Notes:

Min.

www.te.com