

### Buchanan WireMate

TE Internal #: 2834080-1 PCB Terminal Blocks, Receptacle, Wire-to-Board, 2 Position, 1 Row, 90° Wire Entry Angle, 28 – 12 AWG Wire Size, Operating Voltage 300 VAC

#### View on TE.com >

Connectors > Terminal Blocks & Strips > PCB Terminal Blocks



Terminal Block Connector Type: Receptacle

Connector System: Wire-to-Board

Number of Positions: 2

Number of Rows: 1

Wire Entry Angle: 90°

## Features



### Product Type Features

Terminal Block Connector Type	Receptacle
Connector System	Wire-to-Board
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Wire Entry Location	Side
Number of Positions	2
Number of Rows	1
Wire Entry Angle	90°
Electrical Characteristics	
Operating Voltage	300 VAC
Body Features	
Primary Product Color	Gray
Product Orientation	Vertical

### 2834080-1

PCB Terminal Blocks, Receptacle, Wire-to-Board, 2 Position, 1 Row, 90° Wire Entry Angle, 28 – 12 AWG Wire Size, Operating Voltage 300 VAC



### **Contact Features**

Contact Mating Area Plating Material	Tin
Contact Base Material	Copper
Contact Current Rating (Max)	20 A
Termination Features	
Termination Method to Printed Circuit Board	Through Hole - Solder
Termination Method to Wire & Cable	Push-in
Housing Features	
Housing Material	High Temperature Nylon or Polyester
Dimensions	
Wire Size	28 – 12 AWG
Usage Conditions	
Operating Temperature Range	-40 – 105 °C[-40 – 221 °F]
Operation/Application	
Circuit Application	Power & Signal
Packaging Features	
Packaging Method	Box & Carton

# Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 260°C
Product Compliance Disclaimer	

### 2834080-1

PCB Terminal Blocks, Receptacle, Wire-to-Board, 2 Position, 1 Row, 90° Wire Entry Angle, 28 – 12 AWG Wire Size, Operating Voltage 300 VAC



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**



TE Part # CAT-B8519-P7565 Poke-In Connector, BUCHANAN WireMate



TE Part # CAT-SL36-M6642B Miniature Headers, SlimSeal



TE Part # 2834334-2 4.0PITCH ITB CONN\_2P\_W CAP\_NATURAL



TE Part # 2834167-3 RELEASABLE SLIM CONTACT



# Customers Also Bought



### 2834080-1

PCB Terminal Blocks, Receptacle, Wire-to-Board, 2 Position, 1 Row, 90° Wire Entry Angle, 28 – 12 AWG Wire Size, Operating Voltage 300 VAC





## Documents

### Product Drawings 5.0MM SIDE ENTRY MSC 2P\_GY

English

### **CAD** Files

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_2834080-1\_A.2d\_dxf.zip

English

Customer View Model

ENG\_CVM\_CVM\_2834080-1\_A.3d\_igs.zip

English

Customer View Model

### ENG\_CVM\_CVM\_2834080-1\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages Modular Screwless Terminal Blocks Flyer (Chinese)

**BUCHANAN WireMate Connectors Brochure** 

BUCHANAN WireMate Connectors Brochure

English

Modular Screwless Terminal Blocks Flyer

English