

Harax PG 13,5/ panel feed through / 3-po



| - | |
|--------------------|--|
| Part number | 21 01 130 3023 |
| Specification | Harax PG 13,5/ panel feed through / 3-po |
| HARTING eCatalogue | https://b2b.harting.com/21011303023 |

Image is for illustration purposes only. Please refer to product description.

Version

| Termination method | HARAX [®] connection technology |
|--------------------|--|
| Shielding | Unshielded |
| Number of contacts | 2 |
| PE contact | Yes |

Technical characteristics

| Conductor cross-section | 0.75 1.5 mm² |
|--|--------------------|
| Conductor cross-section | AWG 18 AWG 16 |
| Wire outer diameter | ≤2.8 mm |
| Rated current | 16 A |
| Rated voltage conductor-earth | 230 V |
| Rated voltage conductor-conductor | 400 V |
| Rated impulse voltage | 4 kV |
| Pollution degree | 3 |
| Overvoltage category | III |
| Insulation resistance | >10 ⁸ Ω |
| Contact resistance | ≤10 mΩ |
| Limiting temperature | -25 +85 °C |
| Degree of protection acc. to IEC 60529 | IP67 |
| Size | Pg 13.5 |
| Cable diameter | 6 9 mm |
| Isolation group | I (600 ≤ CTI) |
| | |

Page 1 / 2 | Creation date 2023-03-02 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com



Material properties

| Material (insert) | Polyamide (PA) Thermoplastic polyurethane (TPU) |
|--------------------------------------|--|
| Material (contacts) | Copper alloy |
| Surface (contacts) | Gold plated |
| Material (hood/housing) | Polyamide (PA) Thermoplastic polyurethane (TPU) |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Not contained |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Nickel Naphthalene |

Specifications and approvals

| UL / CSA | UL 1977 ECBT2.E102079 CSA-C22.2 No. 182.3 ECBT8.E102079 |
|--------------------------------|---|
| Commercial data | |
| Packaging size | 1 |
| Net weight | 24 g |
| Country of origin | Germany |
| European customs tariff number | 85366990 |
| GTIN | 5713140136779 |
| eCl@ss | 27440103 Sensor-actuator connector chassis (sensor technology acc.) |