

20 19 18 17 16 15 14 13 12 11 9 8 7 6 5 4 3 2 1

VIEW ON MATING SIDE



A = 8 STANDARD CONTACTS L = 3
 C = 8 STANDARD CONTACTS L = 3
 S = 16 TOTAL NUMBER OF CONTACTS

MARKING	STANDARD
PERFORMANCE LEVEL	G2/O = CONTACT AREA LEVEL2 / TERMINATION TIN
FLUX PROOF	NO
FICING CLIP	NO
DIMENSIONS	SD-85003-0002 SHT 1

C	G2/O	c2,4,6,8,10,12,14,16
A	G2/O	c2,4,6,8,10,12,14,16
CONTACT SYMBOL	PERFORMANCE LEVEL	CONTACT POSITION NUMBER

EC NO. I 2004-XXXX DRAWN N.S. 09/09/03 CHK'd G.L. 09/09/03 APPR. G.L. 09/09/03	QUALITY SYMBOLS MAJOR \blacktriangledown CRITICAL ∇	GENERAL TOLERANCES: (UNLESS SPECIFIED)		SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION	DIMENSIONS:			SHT	REV	
		4 PLACES $\pm 0.$	$\pm.$	mm	INCH		<input checked="" type="checkbox"/> mm	<input type="checkbox"/> INCH	<input type="checkbox"/> mm	<input checked="" type="checkbox"/> mm	<input type="checkbox"/> INCH	REVISE ON CAD ONLY
B	REV	DRAWN BY & DATE N.S. 18/09/02		CHECKED BY & DATE G.L. 18/09/02		APPROVED BY & DATE G.L. 18/09/02		TITLE: 48 POS MALE CONNECTOR ACCORDING DIN 41612 STYLE C/2 CONTACTS ARRANGEMENT			SHEET NO. 1 OF 1	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		ANGULAR \pm		CAD FILENAME SD-85003-0531.S0	MATERIAL NO. 85003-0531	DRAWING NO. SD-85003-0531		MOLEX INCORPORATED				
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.												

19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1