### S41F1C-P05MJG0-300S

# series\_f, type\_s4




#### **General information**

| Part number       | S41F1C-P05MJG0-300S |
|-------------------|---------------------|
| Termination       | solder              |
| Size              | 1                   |
| Locking principle | push                |
| Coding            | 1_halfshell         |
| Cable Diameter    | cable_mini_30       |
| Cable outlet      | bend_relief         |









# Contact insert description

| Number of contacts   | 5      |
|----------------------|--------|
| Contact type         | pins   |
| Contact diameter     | 09mm   |
| Insulator material   | peek   |
| Wire cross section   | 22_awg |
| Termination          | solder |
| Termination diameter | 085mm  |

 $reverse\_gender\_on\_request$ 

### **Technical information**

| Max. creepage and air clearance distance | 08_mm     | 08 <sub>_</sub> mm |
|--|-----------|--------------------|
| Nominal current single contact           | 075_a     | iec_60512_5_2      |
| Nominal current insert                   | 5,625 A   | vde_0298_4         |
| Test voltage                             | 135_kv_ac | sae_13441          |

safety\_text

# Mechanical and environmental data

| Degree of protection* | ip68     |
|-----------------------|----------|
| Operating temperature | 40_120_c |
| Mating cycles         | 5000     |

mated

## Material and surface treatments

| Housing | m_chrome      |
|---------|---------------|
| Contact | cu_alloy_gold |

safety\_text\_2 ul\_text illustrative\_text