1201 17/63

APPLICATOR PARTS LIST

TYPE: SIDE FEED STRIPPER CRIMPER

AMP INCORPORATED
HARRISBURG, PENNA.

NO.	DESCRIPTION	REQ.	PART NO.
1	■ WIRE CRIMPER	1	694862-9
2	■ INS. CRIMPER	1	454686-3
3	■ ANVIL	1	2-565063-3
4	Stabilizer		
5	■ SHEAR, Floating	1	1-694851-2
6	■ REAR SHEAR PLATE		
7	SHEAR BLADE SPACER		
8	■ FRONT SHEAR PLATE		
9	REAR ANVIL SPACER PLT.		
10	FRONT ANVIL SPACER PLT.		
11	TOOL SPACER	1	694839-5
12	CRIMP SPACER	1	1-694839-0
13	Stabilizer Spacer		
14	REAR STRIP GUIDE		
15	RAM		
16	TOOL HOLDER		
17	Crimper Holder	1	694856-1
18	ADJ. BLOCK		
19	APPLICATOR MOUNT ASSY.		
20	BASE PLATE		
21	BASE BLOCK		
22	STRIP GUIDE PLATE	1	453309-7
23	ANVIL HOLDER		
24	AUX. ANVIL HOLDER		
25	STRIPPER △1	1	694829-1
26	STRIPPER MOUNT		
27	RETAINER PLATE		
28	STRIPPER MOUNT BRACKET		
29	STRIPPER BUSHING		
30	STOCK DRAG	1	2-694826-3
31	STOCK DRAG HANDLE		
32	STOCK DRAG STUD		
33	STOCK DRAG SPRING		
34	STOCK DRAG ADJ. SCREW		
35	FEED FINGER HOLDER		
36	FEED FINGER		
37	FEED FINGER TIP		
38	FEED FINGER SPACER		
39	BASE CASTING		
40	GUARD		
41			

NO.	DESCRIPTION	REQ.	PART NO.
42			
43			
44	■Wire Grip - Lower △2	Ref	694847-2
45	Retainer, Strip	1	454739-2
46	Post, Retainer	1	694868-1
47			
48			
49			
50	Lever	1	694814-3
51			
52			
53			
54			
55			
56			
57			
58			
59	Rear Shear Assy.		
60	Applicator Assy.	1	694861-7
61	■Blade, Strip LH #26	1	462218-8
62	■Blade, Strip RH #26	1	462217-8
63	■Stabilizer, Wire	1	453262-3
64			
65			
	MISCELLANEOUS		
66			
67	Identification Plate	1	452373-1
68	Lubricator Assy.	1	465184-[illegible]
69	Oil, Synthetic	REF	252931-2
70	Grease, High Pressure	1	24482-2
71			
72			

REV.	REVISION RECORD	DATE	BY	ECN
A	Redrawn	7-3-75	[illegible]	R1198
B	Rev per ECN	4-1-76	[illegible]	R1615
B1	INACTIVATED	7-28-76	[illegible]	R1758
C	EC-A-272490	10-10-90	[illegible]	—
D	EC A-360692	4-2-92	[illegible]	—

CRIMPING DATA

TO APPLY TERMINAL: .093 DIA RECEPTACLE

WIRE SIZE	CRIMP HEIGHT
.26	.029
28	.029

CRIMP	SIZE	TYPE	FEED
WIRE	.055	F	.405
INSUL.	.090	F	
SLEEVED			

INSULATION RANGE: .032-.057
WIRE RANGE: 26-28

EXPLODED VIEW: CM 5210 Sect. 9

REMARKS:
△1 Position between items 1 & 2
△2 See Customer Manual for orientation.
3 Sequence from Ram: 11, 1, 12, 17(2)

TERMINALS: 350221

— INACTIVE —
FOR REPLACEMENT ONLY

■ DENOTES WEARING PARTS
RECOMMEND PURCHASE REPLACEMENT

THIS APPLICATOR IS TO BE USED ON
AMP-O-LECTRIC 694873-1

DIST. 4

SERIAL NO. | DATE SHIPPED

DESIGNED BAC 7/3/75

CUSTOMER NAME AND ADDRESS

CHK'D. TB 7-75

APP'D. BAC 7/3/75

APPLICATOR NUMBER | REV. D 566173-1 | SHEET 1 OF 1