

LEDiL[®]

From Light to Lighting
Q2/2016 Innovations from LEDiL



www.ledil.com

LEDiL's new solderless connectors

YES! Finally connectors and optics from the same manufacturer



What makes you want it?

- Compatibility NOW and in the future with most of our lenses and reflectors
- Multiple dimensions and Zhaga mounting holes
- At VERY attractive price


Technical details

- Robust design allows the product to be used in presence of vibrations and even in high temperature conditions
- LEDiL "snap in" feature simplifies the installation and makes alignment of the LED easy
- Zhaga 35mm and 45mm mounting holes available and the same "twist and lock" features as LEDiL other holder system
- Industrial standard integrated poke-in wire terminals and very low profile design

Make your connections more versatile, robust and future proof

VESUVIUS (D=50mm)

- Metal holding clips that ensure excellent thermal control and pressure against bigger COBs
- Compatible with various lenses and reflectors from LEDiL (ANGELETTE, ANGELA, ANGELINA, RONDA)
- Two socket versions compatible with a range of LEDs from various manufacturers
- Shares the same mounting interface as Ideal, TYCO, Stucchi etc.



LED Compatibility
KA15411_VESUVIUS-A

- CLL163v/CLL03v
- ZC-12/18
- SLE65/LES15
- CXM-14/AC001

Version B
CXA18

And more is coming...

HEKLA (D=44mm)

- Innovative LEDiL Push-In accessories allows you to decide whether you want to solder the LEDs or not
- Push-In accessories are easily adaptable to most existing LEDiL holder systems
- Compatible with smaller size lenses and reflectors like LEDiL's BROOKE- and WINNIE-families
- Minimalistic design with great flexibility



LED Compatibility

KN15490_KONNKTAKT-HEKLA-A-V8

EMR V68

KN15503_KONNKTAKT-HEKLA-A-V13

EMR V1013

KN15502_KONNKTAKT-HEKLA-A-CXA1520

CXA1520

KN15500_KONNKTAKT-HEKLA-A-CXA1850

CXA1850

KN15501_KONNKTAKT-HEKLA-A-CLL020

CLL020/CLL030v

CLL020

CXA1310

CXM-9/AC001

Solera 59

LED029180085

ZC-4/2C-6

SLE-65/LES6/SLE-65

LES11

And more is coming...

LEDiL recommends the use of M3 washers with all solderless connectors to improve reliability and LED lifetime.

Available in Q2

FWHM angles, efficiencies and cd/lm values contained herein are typical values. Actual measured values depend of the specific LED/optic combination. Go to www.ledil.com for LED specific values and optical datasheets.



~360° silicone optic for retrofits

ZORYA

- Omnidirectional lens fulfilling Energy Star standards
- Easy ingress protection due to silicone technology
- Twist and lock holder system allows the lens to be used with solderless connectors

**PATENT
PENDING**



FEATURES & BENEFITS




- High efficiency (95%) with excellent UV, heat, and impact resistance
- Flexible design with 2 dimensions available – 50 and 22mm
- Can be used as it is, or with external protective cover
- RGB and tunable white support
- Flexible design – lens can be scaled and holder modified

COMPATIBILITY

- LES sizes from 6 mm to 24 mm
- Stucchi, BJB and Tyco solderless connectors
- 40 and 50 mm LEDiL adapters

TYPICAL APPLICATIONS

- Retrofit
- Walkway lighting
- Industrial lighting
- Garden lights



LED Compatibility	
BXRAESR, V10, V13	
CLL02x, CLL03x, CLL04x, CLL700, CLL710, CLL720, CLL730	
CXA/B 13xx, CXA/B 15xx, CXA/B 1816, CXA/B 25xx, CXA/B 30xx	
LXCoB 105/107/109, LXCoB 1204/1205, LXCoB 1211	
Soleriq P6, Soleriq P9, Soleriq S13, Soleriq S13 Gen2, Soleriq S19	
LC013B, LC019B	
ZC12/18, ZC25/40, ZC4/6	
Mega Zenerigata, Mini Zenerigata	
SLE 64 LES10, SLE 65 LES15	
DMC 122, DMC 125, DMC 128	

Available in Q2



70mm COB optic with 10° beam and no halo

CARMEN

- Patent pending hybrid lens family with 10° ultra narrow beam
- Higher performance compared to similar metallized reflector designs in the market
- Dust- and TouchProof design

PATENT PENDING



FEATURES & BENEFITS




- No halos or light spilling resulting in a higher intensity and less glare
- Standard retail and track lighting beams available
- Comes with a black reflector, especially optimized for low UGR applications

TYPICAL APPLICATIONS

- Track lighting
- Retail and supermarkets
- Industrial lighting
- Outdoor architectural
- General indoor lighting

COMPATIBILITY

- LES sizes up to 14 mm
- LEDiL recommends spot version to be used with 6mm LES (=18000cd)
- Holder options for BJB and Stucchi solderless connectors



DESIGN EXAMPLE



Ultra narrow beam available

Available in Q2

FWHM angles, efficiencies and cd/lm values contained herein are typical values. Actual measured values depend of the specific LED/ optic combination. Go to www.ledil.com for LED specific values and optical datasheets.



70mm, recessed system for all architectural lighting needs

RONDA

- Asymmetric and double asymmetric wall washing beams meeting even strictest vertical illuminance requirements
- No shadows, uniform light up to the ceiling level without any tilting of the fixture needed
- Wide customization possibilities (front panel, assembly depth, light pattern)

**PATENT
PENDING**



FEATURES & BENEFITS

- Various light distributions available with smooth cut-off
- Low profile design for shallow depth installations
- Typical installation ratio 1:3 with asymmetric beams
- Accessories available by request (black shade available for double asymmetric version)
- ZT45-version for corridors, aisles and vertical surface illumination

MOUNTING OPTIONS

- Screws
- Glue

COMPATIBILITY

- LES sizes up to ~16 mm
- Two holder versions to support most common connectors

Holder A: LEDiL, TE, BENDER+WIRTH and other twist and lock socket types

Holder B: different connectors from BJB and Stucchi





TYPICAL APPLICATIONS

- Office lighting
- Architectural lighting
- Downlights
- Museums
- Shops
- Hotels



LED Compatibility	
V10, VERO13	
CLL02x	
CLU700, CLU710	
CXA/B 13xx	
CXA/B 15xx	
CXA/B 1816	
CXA/B 1830	
LX CoB 1202/1203	
LX CoB 1202s	
NSBxL066A/NFCxL036B	
NSBxL110	
NSCxL036A	
DurisS10	
SolenisS13	
SolenisS9	
Mini Zenigata	

Design example



Available now



Anti-glare Optics with <math><19</math> UGR FLORENTINA family



- Hybrid design of a black reflector and lenses designed for high visual comfort applications
- Higher intensity and less spill light compared to metallized reflectors
- Various mounting options and beam angles available

FEATURES & BENEFITS

- Single lens, 4x1, 2x2 and 12x1 configurations available
- Beams available from 10° to 60°, also asymmetric and double asymmetric
- Standard LEDiL faceplates in black or white and possibility to make your own faceplate
- Versions available with + -30 degrees adjustable rotation mechanism
- Mounting with steel springs or screws to ceiling or to aluminum profile with LEDiL clips

COMPATIBILITY

- LEDiL standard ROSE (up to 5050) lenses available for FLORENTINA 4x1 and 2x2 versions
- LEDiL standard TINA/TINA2 (up to 3535) lenses available for FLORENTINA 12x1

LED Compatibility FLORENTINA-12x1

XHP35 HD, XM-L	LXMZ, LX Rebel ES	Duris S8
XP-E2, XP-G, XP-G2	LX Rebel Plus	Oslon Square EC
XP-L, XD-E, XD-E HI	LXTX, LXZ ES	Oslon SSL 80
LH351B	NC5xx19B	H35C11, EMMW33
TL114	NV5xx19B/NV5xx19C	

LED Compatibility FLORENTINA-1, -2X2, -4X1

XHP35 HD	NV5xx19B/	Oslon Square EC
XP-G2, XP-L	NV5xx19C	LX MZ, LXTX

TYPICAL APPLICATIONS

- Office lighting
- Retail lighting
- Downlight applications
- Track lighting
- Indoor architectural lighting

MOUNTING OPTIONS

- Can be installed into an aluminium profile
- Screws (M3, M4 and PT)
- Press fit pins
- Springs
- Clips
- Glue


ROSE-MRK – Quality lighting for bigger LEDs

COMPATIBILITY


- Super high-power multi-crystal LEDs up to 7070 packages

TYPICAL APPLICATIONS


- Indoor lighting
- General lighting
- Spot lights
- Up- and downlights




Typ. efficiency of 80%



Typ. efficiency of 84%



Typ. efficiency of 84%



Typ. efficiency of 87%


Available now

FWHM angles, efficiencies and cd/lm values contained herein are typical values. Actual measured values depend of the specific LED/optic combination. Go to www.ledil.com for LED specific values and optical datasheets.




FLORENTINA for ROSE-CMC and -MRK lenses

40mm



FLORENTINA-1
C15426_FLORENTINA-1-HLD
C15427_FLORENTINA-1-SHD-60
ROSE lens

MAKE
IT
YOURS



FLORENTINA-2X2


C14735_FLORENTINA-2X2-HLD
C14734_FLORENTINA-2X2-SHD
C14960_FLORENTINA-2X2-SHD-WHT
4 x ROSE lens

FLORENTINA-2X2-UV

C14735_FLORENTINA-2X2-HLD
C15030_FLORENTINA-2X2-SHD-UV
4 x ROSE lens

FLORENTINA-2X2-OPEN

C14735_FLORENTINA-2X2-HLD
C15196_FLORENTINA-2X2-SHD-OPEN
4 x ROSE lens



FLORENTINA-4X1

C15029_FLORENTINA-4X1-HLD
C15028_FLORENTINA-4X1-SHD
4 x ROSE lens

FLORENTINA-4X1-UV

C15029_FLORENTINA-4X1-HLD
C15031_FLORENTINA-4X1-SHD-UV
4 x ROSE lens

FLORENTINA-4X1-OPEN

C15029_FLORENTINA-4X1-HLD
C15198_FLORENTINA-4X1-SHD-OPEN
4 x ROSE lens



FLORENTINA for TINA/TINA2 lenses

FLORENTINA 12x1



C14465_FLORENTINA-HLD
C16446_FLORENTINA-SHD
12 x TINA lens




Available in Q2



10 degree beam with 5050 packages

LUCIA family (90x90mm)

- 4-up lens module with specially tilted lenses
- Precise "blade" type beam ideal for the illumination of large buildings, objects and pillars
- LUCIA can be also used in surgical- and sports lighting applications thanks to its very good cut off




FEATURES & BENEFITS

- Glare-free and powerful light from very compact source
- Specifically optimised for visually demanding tasks
- Easy mounting with 1 screw

TYPICAL APPLICATIONS


- Outdoor up-/downlighting
- Architectural lighting
- Surgery light
- Flood light
- High-speed camera lighting



COMPATIBILITY


- Up to 7070 size LED packages

LED Compatibility		Duvs P10
XHP35 HI, XHP50	XP-E2, XP-G2	LXM, LXMZ
XHP70, XM-L RGB	XP-L	LXZ RGB



COB street and high bay lighting

STELLA silicone lens family (D=90mm)



FEATURES & BENEFITS

- Various beam angles available
- Self-sealing IP67 rated products with excellent thermal, UV, and impact resistance
- Highly performing silicone lenses with no house-side peaks

COMPATIBILITY

- Up to 23mm LES sizes

TYPICAL APPLICATIONS

- Street lighting (ME1 & Type III)
- High Bay (40, 60, 90, 140)
- Canopy and forward throw available

Available now

LED Compatibility: Check www.ledil.com/stellafamily

FWHM angles, efficiencies and cd/lm values contained herein are typical values. Actual measured values depend of the specific LED/optic combination. Go to www.ledil.com for LED specific values and optical datasheets.



Silicone molded 2x2 lenses for high temperature applications

STRADA-2X2MXS (7070 packages)



FEATURES & BENEFITS


- Part of LEDiL standard (90x90mm) 2X2MX platform now in silicone
- High UV, thermal and impact resistance
- Completely sealed structure with 8 screws for IP67

COMPATIBILITY

- Up to 7070 size LED packages
- A range of 2X2MX compliant heatsinks and PCBs available from selected ecosystem partners

TYPICAL APPLICATIONS

- Both indoor and outdoor applications
- Halls, arenas, roads, pathways etc.
- Applications with high lumen outputs



LED Compatibility **XHP70** **LXM**

Available now

STRADA-2X2S (5050 packages)

FEATURES & BENEFITS


- LEDiL standard (50x50mm) STRADA-2X2 footprint in silicone
- High UV, thermal and impact resistance
- Fastening with one M3 screw

COMPATIBILITY

- Optimized for a range of 3535 high power and compatible up to 5050 LED packages

TYPICAL APPLICATIONS

- Street lighting
- Outdoor area lighting
- Pathway lighting



FN15180_STRADA-2X2S-T3

- Smooth uniform rectangular beam
- IESNA Type 3 light distribution and universal solution for general ME classes
- Installation up to 1:5 pole ratio

LED Compatibility

XB-D, XHP35 HD	XP-L, HL, XQ-E, H	NI56x119B/NI56x119C
XHP35 Hi	XI-E, XT-E, HW	Dumis SP
XP-G2, XP-L	LXMZ, LXTX	Oscon Square PC

Available in Q2



Mid power street lighting STRADELLA-8UP

STRADA's little sister – Compact STRADELLA lens doubles the density of LEDs compared to standardized STRADA-2X2 lenses, making it a cost efficient and feasible solution for mid-power LEDs.



FEATURES & BENEFITS


- The same dimensions and mounting hole as STRADA-2X2 family, but with 8 lenses in one
- Standard street lighting and high bay beams available
- Single lens available with the same beam angles

COMPATIBILITY


- STRADELLA-8UP: 3030 & 3535 size packages

TYPICAL APPLICATIONS

- Street lighting (ME, T2 & T3)
- High bay lighting (30, 60, 90)
- Flood lighting




Single lens
For high-power LEDs



8-up module
For high-/mid-power LEDs


Available in Q2



LED Compatibility

- XP-G2
- XT-E
- LX 3030 2D
- LX 3535 2D
- LX FlipChip
- LX FlipChip White 1D
- NP-Z751D
- NP-S519B/N/S5x19C
- Diana S8 1/2 chip
- Oscon Square EC
- Oscon Square Gen3
- Z8Y15, Z8Y19

Available now



FWHM angles, efficiencies and cd/lm values contained herein are typical values. Actual measured values depend of the specific LED/optic combination. Go to www.ledil.com for LED specific values and optical datasheets.


And many more!

Standard LEDiL range of optics expanded





Available in Q2
D: 286 x 61 mm H: 11,4 mm

FLORENCE-ZT25-S
Asymmetric wall washing beam available for Florence-3R product family




Available in Q2
D: 282 x 19 mm H: 6,9 mm

FLORENCE-1R-GC
Minimum glare and optimized LED layout for high-end office lighting




Available now
D: 286 x 61 mm H: 8,45 mm

FLORENCE-O
Elliptical beam now available for high racking applications and corridors





Available now
D: 50 mm H: 9,02 mm

STRADA-2X2-T4-B
Widest IESNA Type IV forward throwing beam



Available in Q2
D: 50 mm H: 13,7 mm

SAGA-S-WHT
Innovative hybrid spotlight with durable silicone lens and reflective white frame for indoor lighting



**YOUR
FASTLANE
TO
MARKET**



Available now

ANGELETTE
Industry standard (D:110 mm) diameter reflectors with various accessories



Available in Q2

BROOKE-G2
Finally Brooke (D:45mm) reflector family is available for next generation COBs



D: 9,9 x 9,9 mm H: 7,5 mm


Available now

LARISA-PIN
New holder available for LARISA product family with LEDiL standard position pins

Where to buy

North America	us.sales@ledil.com	+358 40 413 9990	Sales and Technical Support
Andrey Vasilyev	andrey.vasilyev@ledil.com	+1 (617) 599 0115	Northeast US, Canada
Pasi Kontto	pasi.kontto@ledil.com	+358 40 776 2149	Mid-Atlantic states
Steve Howie	steve.howie@ledil.com	+1 (704) 309 0368	Regional Sales Manager, South-East USA
Lauri Haarala	lauri.haarala@ledil.com	+358 40 653 7666	Midwestern US Balkans
Bruno Musolino	bruno.musolino@ledil.com	+55 (11) 9 8264 6688	Brazil
Jen John Lee	jen.lee@ledil.com	+55 (11) 9 7378 8874	Brazil
Raúl Parra	raul.parra@ledil.com	+358 40 095 6839	Central America, South-America Greece
Rodrigo Menabrito	rodrigo.menabrito@ledil.com	+52 (81) 1609 2329	México
Ville Saarinen	ville.saarinen@ledil.com	+358 40 732 8705	Nordic, Baltic South-Korea Japan, Taiwan
Simon Aldred	simon.aldred@ledil.com	+44 7540 726 384	UK, Ireland, Benelux
Glenn Bultinck	glenn.bultinck@ledil.com	+33 75 09 78 155	France
Dave Simpson	dave.simpson@ledil.com	+34 607 858 901	Spain, Portugal
Martin Lengwenus	martin.lengwenus@ledil.com	+49 1577 1916641	Germany, Austria, Switzerland
Ewald Sutor	ewald.sutor@ledil.com	+49 173 381 7312	Germany [PLZ 6, 7, 8], Austria, Switzerland
Oliver Klasen	oliver.klasen@ledil.com	+49 151 20 66 1985	Germany [PLZ 0-5, 9]
Marcin Wiewiórka	marcin.wiewiorka@ledil.com	+48 501 765 576	Poland, Czech Republic, Slovakia
Diego Quadrio	diego.quadrio@ledil.com	+39 340 659 9236	Italy
Nonna Raita	nonna.raita@ledil.com		Eastern Europe
Saken Jusupov	saken.jusupov@ledil.com	+7 911 758 95 54	Russia, Ukraine, Belarus, Kazakhstan
Zekeriya Boz	zekeriya.boz@ledil.com	+90 546 291 2 444	Turkey & ME
Bahador Mozaffari	bahador.mozaffari@ledil.com	+98 912 593 9355	Iran
Joni Mäki	joni.maki@ledil.com	+358 40 413 9990	Global
Tang Yunfeng	yunfeng.tang@ledil.com	+86 139 1727 3224	China, Hong Kong, Taiwan, Mongolia
Suppaluck Sae-Sean	suppaluck.sae-sean@ledil.com	+66 869 741 968	Thailand, Malaysia
Sampsa Nurmi	sampsa.nurmi@ledil.com	+358 41 503 5316	Global

For detailed information visit www.ledil.com/where_to_buy



Installation guide



YouTube

For technical
support and
simulations

contact us at:

tech.support@ledil.com