ATGBICS QFX-QSFP-40G-ESR4 Juniper Compatible Transceiver QSFP+ 40GBase-CSR4 (850nm, MMF, 400m, MTP/MPO, DOM)

Brand : ATGBICS

Product code: QFX-QSFP-40G-ESR4-C

Product name : QFX-QSFP-40G-ESR4 Juniper Compatible Transceiver QSFP+ 40GBase-CSR4 (850nm, MMF, 400m, MTP/MPO, DOM)

QFX-QSFP-40G-ESR4 Juniper Compatible Transceiver QSFP+ 40GBase-CSR4 (850nm, MMF, 400m, MTP/MPO, DOM)


ATGBICS QFX-QSFP-40G-ESR4 Juniper Compatible Transceiver QSFP+ 40GBase-CSR4 (850nm, MMF, 400m, MTP/MPO, DOM):

ATGBICS QFX-QSFP-40G-ESR4 40GBase-SR4 supports a distance of up to 400m over multi mode fibre (MMF) using a wavelength of 850nm via an MPO connector. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product meets the specification of QFX-QSFP-40G-ESR4= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.





Performance		Features	
SFP transceiver type *Fiber opticMaximum data transfer rate *40000 Mbit/sInterface type *QSFP+Single-mode fiber (SMF) supported*Multi-mode fiber (MMF) supported*Fiber optic connectorMPOSFP transceiver standardSRMaximum transfer distance400 mWavelength\$50 nmEthernet LAN*Digital Diagnostics Monitoring (DDM)*Wavelength-division multiplexing (WDM)*FeaturesSilverProduct colourSilverHousing material Plug and Play*	40000 Mbit/s	Certification	CE, FCC, RoHS
		Power	
	×	Input voltage Maximum voltage Power consumption (typical)	3.3 V 3.5 V 3.5 W
		Operational conditions	
	Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Weight & dimensions Width Depth Height	70 °C 0 - 70 °C -40 - 85 °C 0 - 95% 0 - 95% 13.5 mm 72.4 mm 18.4 mm	
		Weight	42 g
	1	Packaging data	
Hot-Plug support	4	Number of products included	1 pc(s)
Hot-swap	4	Package type	Box
Easy to install	✔ United Kingdom Juniper	Technical details	
, ,		Sustainability compliance Sustainability certificates Doesn't contain	✔ RoHS Lead



5056468715937

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.