



- 3 Type**
- A** With flange for surface mounting
 - B** With internal thread
 - C** With male thread

Metric table

Dimensions in: millimeters - inches

1 d	2 r	b	$l_1 \approx$	l_2	l_3 min.	l_4
17 0.67	40 1.57	10 0.39	5.5 0.22	16.5 0.65	21.5 0.85	11 0.43
17 0.67	55 2.17	10 0.39	5.5 0.22	16.5 0.65	21.5 0.85	11 0.43

Specification

- Latch arm
Zinc die-cast
Powder coated
Black, RAL 9005, textured finish
Red, RAL 3000, textured finish
- Indexing mechanism
 - Type A
Zinc die-cast / plastic
 - Type B, C
Steel / plastic, steel parts zinc plated, blue passivated finish
- Screw-on flange
Zinc die-cast
Powder coated
Black, matte finish
- RoHS compliant

Information

GN 702 stop latches offer a fast and easy way to close and hold doors, flaps, slide-in modules, etc. They latch in four positions (90°).

Type C stop latches have the same connecting dimensions as GN 115.1 and GN 115.6 mini latches. The mounting bores are to be selected accordingly.

The installation bore hole in the door leaf is usually generated by punching or laser machining during a mass production run.

For small production runs and steel sheets below 2 mm thickness, the GN 123 sheet metal punches are the tool of choice.

The mounting bore holes can also be made by drilling or milling.

How to order	1 Handle diameter d
1	Length r
2	Type
3	Color
4	

GN 702-17-40-C-SW