


NOTES:

- 1) LABELS ARE M23053/5 ,WHITE. ACCEPTABLE SUBSTITUTION IS DAT-38-292 OR TRANSVINYL (DAT-63-292-2.5).
- 2) TERMINUS ENFACE REQUIREMENTS SHALL MEET GR-326 AND IEC 61300-3-35.
- 3) MAX IL @ 850 nm SHALL BE 0.5 dB PER CONNECTION.

REVISION HISTORY -- ALL SHEETS ARE AT THE SAME REVISION			
REV	DESCRIPTION	DATE	APPROVED
-	INITIAL RELEASE	2017/11/13	



3	AFSI-PRE T BOX	BOX, SMALL FIBER CABLE 10X10X2 W/AFSI GRAPHICS	1
2	SE001L202C0E-BI	2.0mm 50um OM3 BICABLE, AQUA (SE001L202C0E-BIF)	2 FEET
1	M801-MS1N	ARINC 801 TERMINI, MM127, NON-PULL PROOF	2
ITEM NO.	PART NO.	DESCRIPTION	QTY/ LENGTH

MATERIAL:		DfTR/Designer: C. Hoang	2017/10/23	Amphenol FSI
		Check By: B. Waite	2017/10/24	
		Manufacturing: B. Waite	2017/10/24	
		Market Manager/PLM: Q. Abraham	2017/10/25	
DRILLED HOLE DIAMETER TOLERANCE		Configuration Management: L. Brown	2017/11/13	TITLE: ARINC PIN TO PIN PATCHCORD, MM, 52/125um
DO NOT SCALE DRAWING UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOL ON ANGLES ±3° 1 PL ±.1 2 PL ±.02 3 PL ±.010 INTERPRET DIM AND TOL PER ASME 14.5M-1994		This Document contains proprietary information and such information is prohibited from disclosure to others, publication or duplication in whole or in part without written permission from Amphenol Fiber Systems International. Copyright © 2017 Amphenol Fiber Systems International. Non published work. All rights reserved.		SIZE A
NEXT ASSY	USED ON	CAGE CODE 0YPM2	DWG NO 14100901KC-D1	REV -
APPLICATION		SCALE: NONE	SHEET 1 OF 1	