

HHS-410



Improve compressor efficiency with easy-to-install Hard Start kits from Hartland Controls. Hard Starts allow A/C units and heat pump compressors to start-up at maximum efficiency, so the unit can reach normal rated speed up to ten times faster.

Features

- Use on 1/4 to 1/3 HP HVAC High Efficiency Compressor or Refrigeration Unit
- Ideal solution for replacing three components in a system with a run capacitor
- · Solid State Relay and Capacitor
- Maximum RLA 6.8 Amps
- Easy 5-wire installation
- Helps older compressors start and run cooler
- Easy mount clip or screw mount for quick installation
- UL® Recognized

Specifications

AC Voltage

110-125

Temperature

-40 to +65 Celsius

Capacitance

243-292 µF

Frequency

50/60 Hz


Applications


Hard starting compressor Low voltage situation Works on "RSIR", "CSIR", "PSC" and "CSR" compressors

Replacement Parts	
Replacement Part Number	Manufacturer
RCO410 or HS410	Supco®
35741	Mars®
600-410	Robertshaw®
TQS41	Packard®

Dimensions in millimeters









Model: HHS-410		
Lead Wire Color	Lead Wire Length	Lead Wire End Condition
Black	250mm +/- 8mm	Stipped
Black	250mm +/- 8mm	Stripped
Black	450mm +/- 8mm	Dual (Male/Female) 1/4" QC
Red	450mm +/- 8mm	Dual (Male/Female) 1/4" QC
White	450mm +/- 8mm	Dual (Male/Female) 1/4" QC

We can custom engineer a solution to meet any need. Just ask. 815.626.5170 | HartlandControls.com