

# Contact insert - HC-COM-17-EBUC - 1408478

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



HEAVYCON crimp contact insert for compact plastic housing; socket version; 17-pos. + PE

## Key commercial data

Packing unit	0
Minimum order quantity	2
Catalog page	Page 591 (PC-2011)
GTIN	 4 046356 618182
Custom tariff number	85366990
Country of origin	CHINA

## Technical data

### General data

Note	For crimp contacts CK 1.6-ED...
Connection method	Crimp connection
Ambient temperature (operation)	-40 °C ... 100 °C (including heating up of contacts)
Pollution degree	3
Surge voltage category	III
Number of positions	17
Insertion/withdrawal cycles	≥ 500
Design	COM
Connection in acc. with standard	IEC / EN
Conductor cross section	0.14 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
Connection cross section AWG	26 ... 14
Stripping length of the individual wire	8 mm
Stripping length of the individual wire	6 mm (For 2.5 mm <sup>2</sup> )

### Material data

Inflammability class according to UL 94	V0
Contact material	Copper alloy
Contact surface material	Ag (alternatively Au)
Contact carrier material	PC

### Electrical characteristics

# Contact insert - HC-COM-17-EBUC - 1408478

## Technical data

### Electrical characteristics

Rated voltage (III/3)	200 V
Rated surge voltage	4 kV
Rated current	10 A

## Classifications

### eclass

eCl@ss 4.0	27140816
eCl@ss 4.1	27140816
eCl@ss 5.0	27143424
eCl@ss 5.1	27143424
eCl@ss 6.0	27143424
eCl@ss 7.0	27440209

### etim

ETIM 4.0	EC000437
----------	----------

### unspsc

UNSPSC 6.01	30211923
UNSPSC 7.0901	39121522
UNSPSC 11	39121522
UNSPSC 12.01	39121522
UNSPSC 13.2	39121522

## Approvals

### Approvals

---

#### Approvals

UL Recognized / cUL Recognized / cULus Recognized

---

#### Ex Approvals

---

#### Approvals submitted

---

### Approval details

# Contact insert - HC-COM-17-EBUC - 1408478

## Approvals

UL Recognized	
mm <sup>2</sup> /AWG/kcmil	22-14
Nominal current I <sub>N</sub>	19.5 A
Nominal voltage U <sub>N</sub>	600 V

cUL Recognized	
----------------	--

cULus Recognized	
------------------	--

## Accessories

### Accessories

### Tools

Crimping pliers - CRIMPFOX-1,6/2,5-ED-4,0 - 1687419



Crimping pliers, for turned contacts, CK 1.6 ED... and CK 2.5 ED...

Dummy socket - CK1,6-ED-BB - 1645888



Dummy socket for contact carrier with turned CK 1,6-ED.. female contacts

Removal tool - VC-EW 1,6 - 1884869




Contact removal tool, for turned and rolled CK- 1.6-... contacts

# Contact insert - HC-COM-17-EBUC - 1408478


## Drawings

### Schematic diagram




Connector pin assignment, connection side

### Diagram



Derating diagram for 2.5 mm<sup>2</sup>

### Dimensioned drawing



HC-COM-17-EBUC dimensional drawing